Blade Fuse Block w/ LED Warning Light 6 Position





Specifications

Fuse Holder Type : Blade Fuse Holder Fuse Holder Terminal : Quick Connect

Fuse Size : Blade No. of Fuses : 6 Fuses

Input Terminal Rating : #10-32 Threaded Studs (100A Max.)

Output Terminal Rating : 30A Max. Per Circuit Voltage Rating : 32V DC

ollage Ralling . 32V DC

Connection Pad : Input Wire Size: #4-6AWG
Output Wire Size: #12-16AWG

Torque Rating : 20 in-lb (2.25Nm) Max.

Mounting Torque Rating : 8 in-lb (0.9Nm) Max.


Operating Temperature : -20°C to +85°C


Material Specifications


Housing & Base : PBT, UL94V-0, Black Cover : PC, UL94V-2, Transparent


Push Button : POM, White
Terminal : Copper, Tin Plated


Diagram
















Dimensions : Millimetres


www.element14.com www.farnell.com www.newark.com



Blade Fuse Block w/ LED Warning Light 6 Position



Circuit Diagram



Part Number Table

Description	Part Number
Blade Fuse Block w/ LED Warning Light, 6 Position, Panel Mount, QC	MC002800

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com www.farnell.com www.newark.com

