
Product data sheet Characteristics

ZB5FV043

flush mounted red pilot light head for integral led

Product availability: Stock - Normally stocked in distribution facility





Main

Range of product	Harmony XB5
Product or component type	Head for pilot light
Product compatibility	Integral LED
Device short name	ZB5
Bezel material	Plastic
Mounting diameter	1.18 in (30 mm)
Head type	Built-in-flush
Sale per indivisible quantity	1
Shape of signaling unit head	Round
Cap/Operator or lens colour	Red
Operator additional information	With plain lens

Complementary

OAD II 1:III	4.40 (- (07.111)	-
CAD overall width	1.46 in (37 mm)	
CAD overall height	1.46 in (37 mm)	
CAD overall depth	1.18 in (30 mm)	
Product weight	0.03 lb(US) (0.015 kg)	
Electrical composition code	P1 in front mounting with integral LED P2 in front mounting with integral LED and transformer PF1 in front mounting with integral LED	

Environment

Protective treatment	TH	si nc
Ambient air temperature for storage	-40158 °F (-4070 °C)	— entatic
Ambient air temperature for operation	-40158 °F (-4070 °C)	
Overvoltage category	Class II IEC 60536	— sir
IP degree of protection	IP69 IP67 IP66 conforming to IEC 60529) Sisclaimer: Th

	IP69K
NEMA degree of protection	NEMA 13
	NEMA 4X
Resistance to high pressure washer	1015.26 psi (7000000 Pa) at 131 °F (55 °C),distance: 0.1 m
IK degree of protection	IK03 conforming to IEC 50102
Standards	EN/IEC 60947-5-5
	EN/IEC 60947-5-4
	EN/IEC 60947-5-1
	CSA C22.2 No 14
	UL 508
	JIS C 4520
	EN/IEC 60947-1
Vibration resistance	5 gn (f = 2500 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 18 ms) half sine wave acceleration conforming to IEC 60068-2-27
	50 gn (duration = 11 ms) half sine wave acceleration conforming to IEC 60068-2-27

Ordering and shipping details

Category	22467 - PUSHBUTTONS,22MM(PLASTIC) NEW
Discount Schedule	CS2
GTIN	00785901053828
Nbr. of units in pkg.	1
Package weight(Lbs)	5.999999999998E-2
Returnability	Υ
Country of origin	FR

Offer Sustainability

Sustainable offer status	Green Premium product
	<u>'</u>
RoHS (date code: YYWW)	Compliant - since 0627 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available
California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
More information	For more information go to www.p65warnings.ca.gov