muRata Capacitor Data Sheet RHEL82A103K0A2H03B "#" indicates a package specification code.						
In Production Rectantian AEC- 150 Low acoustic Deflecting crack	Soldering crack Flow OK Welding Re	DHS REACH				
< List of part numbers with package codes > RHEL82A103K0A2H03B						
Shape		Note	es			
	1	Meet LF(Lead Free)[*LF : Lead content is less than 1000 ppm.], HF(Halogen Free)				
ed: 0.5±0.05		Packaging	Specifications	Minimum quantity		
F±0.8		В	Packing in bulk	500		
- Lead Wire : Solder Coated Copper Wire or Solder Coated CP Wire (in mm)						
L size or outer diameter D (mm)	3.6 mm max.					
Wsize	3.5 mm max.					
T size	2.5 mm max.					

2.5 ±0.8mm

0.5 ±0.05mm

Specifications

Lead spacing F

Lead diameter d

Capacitance	10000pF ±10%
Rated voltage	100Vdc
Temperature characteristics (complied standard)	X8L(Murata)
Capacitance change rate	+15/-40%
Temperature range of temperature characteristics	-55 to 150°C
Operating temperature range	-55 to 150°C

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.