## GRM0335C2A7R7BA01# "#" indicates a package specification code.














< List of part numbers with package codes > GRM0335C2A7R7BA01D , GRM0335C2A7R7BA01W , GRM0335C2A7R7BA01J

## **Shape**



| L size         0.6 ±0.03mm           W size         0.3 ±0.03mm           T size         0.3 ±0.03mm           External terminal width e         0.1 to 0.2mm           Distance between external terminals g         0.2mm min.           Size code in inch(mm)         0201 (0603M) | L W                                   |              |
|---|---------------------------------------|--------------|
| T size 0.3 ±0.03mm  External terminal width e 0.1 to 0.2mm  Distance between external terminals g 0.2mm min.  | L size                                | 0.6 ±0.03mm  |
| External terminal width e 0.1 to 0.2mm  Distance between external terminals g 0.2mm min.  | W size                                | 0.3 ±0.03mm  |
| Distance between external terminals g 0.2mm min.  | Tsize                                 | 0.3 ±0.03mm  |
|   | External terminal width e             | 0.1 to 0.2mm |
| Size code in inch(mm) 0201 (0603M)  | Distance between external terminals g | 0.2mm min.   |
|   | Size code in inch(mm)                 | 0201 (0603M) |

## References

| Packaging | Specifications   | Minimum quantity |
|-----------|--|------------------|
| D         | φ180mm Paper taping  | 15000            |
| J         | φ330mm Paper taping  | 50000            |
| W         | φ180mm Paper taping (W8P1*)  * Width: 8mm, Pocket pitch: 1mm | 30000            |

| Mass (typ.) |        |  |
|-------------|--------|--|
| 1 piece     | 0.33mg |  |
| φ180mm Reel | 118g   |  |

## **Specifications**

| Capacitance                                      | 7.7pF ±0.1pF |
|--|--------------|
| Rated voltage                                    | 100Vdc       |
| Temperature characteristics (complied standard)  | C0G(EIA)     |
| Temperature coefficient                          | 0±30ppm/°C   |
| Temperature range of temperature characteristics | 25 to 125°C  |
| Operating temperature range                      | -55 to 125°C |

1 of 2




<sup>1.</sup> This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



<sup>2.</sup> This datasheet has only typical specifications because there is no space for detailed specifications.



2 of 2



1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.