

Part Number: 26800B-223-SPZ

Description: SPZ-50 Stereo Zoom Microscope with OLED Ring Light and Pole Stand

Provides crisp clear 3D images, long working distance and a wide field of view. 6.7x to 50x continuous zoom with 10x eyepieces. When compared to standard LED ring lights, the OLED Ring Light provide reduced glare and a natural light tone. Includes a dimmer control box and a ring light adapter.

System Contents:

SPZ-50 Stereo Zoom Microscope

• 26200B-223: OLED Ring Light

• 26800B-511: Pole Stand



SPZ binocular stereo zoom microscopes offers the best in class zoom ratio with super sharp 3D images, wide field of view and long working distance which makes it an ideal choice for high throughput inspection stations and engineering and science labs.

This system features the OLED Ring Light. When compared to standard LED ring lights, the OLED Ring Light provide reduced glare and a natural light tone.

Wide Magnification Range

Aven's SPZ-50 Stereo Zoom Microscope has a magnification range of 6.7x to 50x, which can be enhanced to up to 200x with optional auxiliary lenses and eyepieces.

Zoom Adjustment

Graduations on the zoom knob tell operators the exact magnifications at which they are working. This is a particularly convenient feature for applications requiring very specific adjustments.

The OLED ring light consists of four Organic Light Emitting Diode (OLED) panels, providing uniform, shadow-free illumination. OLED offers excellent color rendering close to natural light for ideal observation of true-to-life colors.

Each panel can be tilted up and down, allowing for the ideal illumination angles.

This lightweight and compact stand is ideal for examining small parts and where bench space is a premium. The package comes with rack and pinion focus mount with coarse focus knob.

Features:

- Large zoom ratio 7.46:1- best zoom ratio in class
- Field of View 34.3mm to 3.6mm (1.35" to 0.14")
- Working distance 108mm (4.25") the best in class
- 17mm (0.67") high eye point wide field 10x eyepieces (field number 23) for comfortable viewing even for operators with eyeglasses
- Diopter adjustment on both eyepiece tubes
- 4 Organic Light Emitting Diode panels provide even, natural illumination with no glare or shadows
- Includes a dimmer box to control the light intensity
- OLED panels can be tilted up and down to provide the ideal illumination angle
- Light weight compact stand
- Ideal for examining small parts
- Saves bench space
- Comes with rack & pinion focus mount with course adjustment knobs

Specs:

Body Type Binocular, 360° rotatable, 45° inclined eyepiece tube

Eyepieces Two 10x(FN23)eyepieces supplied with microscope body. Optional 15x(FN15) and

20x(FN11.4) available to extend magnification range

Zoom Ratio *7.46:1*

Diopter Adjustment On both eye tubes: +5.6D-.72D

Interpupillary Distance

Adjustable from 52 to 75mm

Optical System Greenough

Color Temperature 5400K

Illuminance at 100mm

MIN 800lx ~ MAX 2,500lx (5,000lx w/tilted panels)

Aperature 41mm – 62mm

27mm – 40mm (with extenders for fixing screws)

Power supply AC Adapter (Input AC 100 – 240V, 50/60Hz)

Rated Voltage DC15V

Power

Consumption 5.5W(MAX)

OLED Life Time Approx. 10,000 hours at middle intensity

Base Size 220mm x 284mm x 15mm

Vertical Post

Length

250mm