

KC series test leads

Wind turbine lightning protection test lead sets



- **Developed in conjunction with a leading manufacturer of wind turbines**
- **Allows easy and reliable measurement of lightning protection circuit resistance of wind turbines**
- **Available in three lengths, 30 m, 60 m and 100 m to suit both manufacturing and maintenance applications**
- **Long cable fitted on strong metal framed cable reel**
- **Cable reel fitted with friction brake to avoid tangles when paying out cable emfs**
- **Uses duplex connect test lead system**

DESCRIPTION

The KC series of test leads provide a complete and convenient solution to the problem of finding reliable test leads that are long enough for testing the continuity of lightning protection conductors in wind turbines.

KC-series wind turbine test leads are available in 100 m, 60 m and 30 m versions that are equally suitable for use on site or in the manufacturing plant. All lead set versions are 10 A rated.

The lead sets consist of two test leads. The first is a 5 m cable fitted with a duplex handspike for probing the lightning receptors on the tips of the turbine blades. The second cable is either, a 30 m, 60 m or 100 m cable, fitted with a large robust Kelvin clip, specially designed to offer ease of use while providing the consistently reliable connections needed to ensure accurate and repeatable test results.

The long cable is wound onto a high quality, robust cable reel fitted with a friction brake to avoid tangles whilst paying out.

ADDITIONAL FEATURES AND BENEFITS

- Hook terminations marked with C or P to assist in making the correct connections
- Duplex handspikes has a compress and rotate action to ensure good connection to lightning receptors
- Cable guide on cable reel to assist with neat re winding
- Light weight, even 100 m long KC100 lead set is less than 15 kg
- Duplex connect test lead system allows probes or clips to be changed quickly and easily on site

APPLICATIONS

This lead set is intended to measure the resistance of the lightning protection circuit of a wind turbine, either in part in a production environment, or fully assembled during commissioning, maintenance, or following repair. This lead set is designed to be connected to any instruments in the Megger 10 A DLRO range or the Megger BT51. However, for outside use the DLRO10HD is recommended due to its robustness and high IP rating.

Lead resistance

- KC30 250 mΩ
- KC60 500 mΩ
- KC100 900 mΩ

ORDERING INFORMATION

Description	Order Code
KC100 Kelvin lead kit (1 x 100 m / 1 x 5 m)	1000-809
KC60 Kelvin lead kit (1 x 60 m / 1 x 5 m)	1001-248
KC30 Kelvin lead kit (1 x 30 m / 1 x 5 m)	1001-249
Optional accessories	
DP1-C Duplex connect probe	1006-450
DTP1-C Duplex connect twist probe	1006-449
CP1-C Concentric duplex connect probe	1006-448
KC1-C Heavy duty kelvin clip	1006-447
KC2-C Insulated connect kelvin clip	1006-451

SALES OFFICE

Megger Limited
Archcliffe Road Dover
CT17 9EN England
T +44 (0) 1304 502101
E UKsales@megger.com

UNITED STATES

4271 Bronze Way
Dallas TX 75237-1019 USA
T 800 723 2861 (USA only)
T +1 214 333 3201
F +1 214 331 7399
USsales@megger.com

OTHER TECHNICAL SALES OFFICES

Valley Forge USA, College Station USA, Sydney AUSTRALIA, Täby SWEDEN, Ontario CANADA, Trappes FRANCE, Oberursel GERMANY, Aargau SWITZERLAND, Kingdom of SAUDI ARABIA, Mumbai INDIA, Johannesburg SOUTH AFRICA, Chonburi THAILAND

CERTIFICATION ISO

Registered to ISO 9001:2008 Cert. no. Q 09250
Registered to ISO 14001:2004 Cert. no. EMS 61597

KC_TEST_LEADS_DS_EN_V04

www.megger.com

Megger is a registered trademark