



Note: This datasheet may be out of date

Please download the latest datasheet of NCP15WD683J03RC from the official website of Murata Manufacturing.

Co., Ltd.

https://www.murata.com/en-eu/products/productdetail?partno=NCP15WD683J03RC

NCP15WD683J03RC












Appearance & Shape







- 1. Excellent solderability and high stability in environment
- 2. Excellent long time aging stability
- 3. High accuracy in resistance and B-Constant
- 4. Reflow soldering possible
- 5. Same B-constant in the same resistance in the three sizes (0805 size / 0603 size / 0402 size)

Easy to use smaller size in the circuits

- 6. Lead is not contained in the product.
- 7. NCP series are recognized by UL/cUL (UL1434, File No.E137188).



Limited Usage	Consumer Grade
Other Usage	Temperature compensation for transistor, IC and crystal oscillator in mobile communications Temperature sensor for rechargeable batteries Temperature compensation of LCD Temperature compensation in general use of electric circuits



Packaging Information

Packaging	Specifications	Minimum Order Quantity
RC	180mm Paper Tape	10000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/11/25

Note: This datasheet may be out of date

 $\underline{ \text{Please download the latest datasheet of NCP15WD683J03RC from the official website of Murata Manufacturing} \\$ Co., Ltd. https://www.murata.com/en-eu/products/productdetail?partno=NCP15WD683J03RC

NCP15WD683J03RC



Resistance (25°C)	68kΩ
Resistance Value Tolerance (at 25°C)	±5%
B-Constant (25/50°C)	4150K
B-Constant (25/50°C) Tolerance	±3%
B-Constant(25/80°C)(Reference Value)	4201K
B-Constant(25/85°C)(Reference Value)	4209K
B-Constant(25/100°C)(Reference Value)	4232K
Max. Voltage	5V
Maximum Operating Current (25°C)	0.038mA
Typical Dissipation Constant (25°C)	1mW/°C
Operating Temperature Range	-40°C to 125°C
Size Code (in mm)	1.0x0.5mm
Shape	SMD
Mass	0.0012g

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering




Note: This datasheet may be out of date


 $\underline{ \text{Please download the latest datasheet of NCP15WD683J03RC from the official website of Murata Manufacturing} \\$

https://www.murata.com/en-eu/products/productdetail?partno=NCP15WD683J03RC

NCP15WD683J03RC







Resistance-Temperature Characteristics

Maximum Operating Voltage Reduction Characteristics

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/