


RoHS
Compliant



Description

This product is a thermally conductive electrically isolating material. Supplied in sheet format with optional adhesive options. Product can also be cut according to specification.

Features

- 1W/mk thermal conductivity
- Very good insulation
- Fire prevention
- Shock resistant

Properties

Characteristic	Value	Test Method
Colour	Grey	Visual
Thickness	0.23mm	-
Thermal Conductivity	1W/mK	ASTM D5470
Hardness (Shore OO)	98	ASTM D2240
Specific Gravity	1.7g/cm ³	ASTM D792
Dielectric Strength	5kV/mm	ASTM D149
Operation Temperature	-50°C to +200°C	EN344
Flame Rating	V-0	UL94

Part Number Table

Description	Part Number
Thermally conductive insulator, Grey, 1W/mK, 300mm × 300mm × 0.23mm	MPGCS-010TCI-300-0.23

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.