muRata Inductor Data Sheet


LQG18HHR15J00# "#" indicates a package specification code.

Power-train an AEC-0200 Cmax. RoHS REACH In Production

< List of part numbers with package codes >

LQG18HHR15J00D , LQG18HHR15J00J , LQG18HHR15J00B





0.8 ±0.15mm

0603 (1608)

Packaging code	Specifications	Minimum quantity
D	φ180mm Paper taping	4000
J	φ330mm Paper taping	10000
В	Packing in bulk	1000

Mass (Typ.)	
1 piece	0.003g

Specifications

Size code in inch (mm)

T size

Inductance	150nH ±5%
Inductance test frequency	100MHz
Rated current (Itemp) (Based on Temperature rise)	300mA
Max. of DC resistance	1.2Ω
Q (min.)	14
Q test frequency	100MHz
Self resonance frequency (min.)	550MHz
Operating temperature range (Self-temperature rise is not included)	-55 to 125°C
Series	LQG18HH_00

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued


without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Chart of characteristic data (The charts below may show another part number which shares its characteristics.)



Q-Frequency characteristics (Typ.)



🔔 Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

2 of 2