


# Measuring instrument - EEM-EM327 - 2908586

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Three-phase power meter for active power measurement with direct measurement in networks of up to 500 V / 80 A, with S0 output, with digital input and MBUS interface, certified in accordance with the MID directive



## Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 338255
GTIN	4055626338255
Weight per Piece (excluding packing)	494.600 g
Custom tariff number	85371098
Country of origin	Italy

## Technical data

### Dimensions

Width	72 mm
Height	90 mm
Depth	67 mm

### Ambient conditions

Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 75 °C
Max. permissible relative humidity (operation)	80 %
Degree of protection	IP51 (Front)
	IP20 (Connections)

### Input data

Designation	Measuring input
Input voltage range	3x 184 V ... 288 V (320 V ... 500 V)
Power consumption	7.5 VA (0.5 W)
Frequency range	45 Hz ... 65 Hz

# Measuring instrument - EEM-EM327 - 2908586

## Technical data

### Input data

Energy (EN 50470-3)	Class B
Real energy (IEC 62053-21)	Class 1
Reactive power (IEC 62053-23)	Class 2
Designation	Digital input
Description of the input	Active opto-isolated
Input voltage range	80 V AC/DC ... 276 V AC/DC

### Output data

Designation	S0 output
Output description	Passive opto-isolated
Maximum switching voltage	27 V DC
Max. switching current	27 mA

### Communication interface

Communication protocol	M-Bus
Communication standard	EN 13757-1-2-3
Transmission speed range	300 bps ... 9600 bps

### General

Degree of protection	IP51 (Front)
	IP20 (Connections)
Protection class	II (EN 50470-1)
Electric strength	6 kV
	4 kV (EN 50470-3, 7.2)

### Connection data

Connection name	Measurement connection
Connection method	Screw connection
Conductor cross section solid	1.5 mm <sup>2</sup> ... 35 mm <sup>2</sup>
Tightening torque	2 Nm

### Connection data 2

Connection name	Other connections
Connection method	Screw connection
Conductor cross section solid	0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Tightening torque	0.5 Nm

### Standards and Regulations

Standards/specifications	EN 50470-1 EN 50470-3
Conformance	CE-compliant
MID	MID-compliant

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
------------	---

# Measuring instrument - EEM-EM327 - 2908586


## Technical data

### Environmental Product Compliance

	No hazardous substances above threshold values
--	--

## Drawings

Connection diagram



## Classifications

### eCl@ss

eCl@ss 5.0	27200307
eCl@ss 5.1	27200307
eCl@ss 6.0	27142300
eCl@ss 7.0	27142330
eCl@ss 8.0	27142330
eCl@ss 9.0	27142330

### ETIM

ETIM 4.0	EC002308
----------	----------

# Measuring instrument - EEM-EM327 - 2908586

## Classifications

### ETIM

ETIM 5.0	EC002308
ETIM 6.0	EC002301
ETIM 7.0	EC002301

## Approvals

### Approvals

---

### Approvals

EAC

---

### Ex Approvals

---

## Approval details

EAC		RU *- DE.A*30.B.01628
-----	---	--------------------------