

LiYv Hook Up Wire

multicomp PRO



**RoHS
Compliant**

This LiYv Hook Up Wire is supplied on 500 metre reels or it can be cut to your desired length in multiples of 1 metre.

Characteristics:

Rated Voltage U_0/U (Um) : 500V
Test Voltage : 2.5kV
Maximum Temperature : Fixed: -40°C to +90°C
Flexible: -50°C to +50°C
Minimum Bending Radius : Fixed: 12 x overall diameter
Oxygen Index : 29%

Cable Standards:

EN 60228, IEC 60332-1, IEC 60332-2, VDE 0812

Construction:

Conductor

Class 5 Stranded tinned copper wires according to EN 60228

Insulation

PVC

Dimensions:

Nominal Cross Sectional Area mm ²	Nominal Overall Diameter mm	Insulation Resistance Minimum MΩ×km
1 × 0.25	1.4	5000

Part Number Table

Description	Nominal Cross Sectional Area mm ²	Part Number
LiYv Hook Up Wire, Black - RAL 9005	1 × 0.25	PP002027
LiYv Hook Up Wire, Red - RAL 3000		PP002028
LiYv Hook Up Wire, Blue - RAL 5015		PP002029
LiYv Hook Up Wire, Green - RAL 6018		PP002030
LiYv Hook Up Wire, White - RAL 9003		PP002031
LiYv Hook Up Wire, Yellow - RAL 1021		PP002032
LiYv Hook Up Wire, Brown - RAL 8023		PP002033

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp PRO