


Coaxial Cable RG405

multicomp^{PRO}

RoHS
Compliant



Construction Specification:

Item	Material	Diameter (mm)
1. Inner conductor	SCCS	0.53 ±0.01
2. Dielectric	PTFE	1.68 ±0.05
3. Outer Conductor	TPC	2.17 ±0.05

Electrical Characteristics:

Items	Data
Capacitance (pF/m)	98
Impedance (ohm)	50 ±2
Velocity (%)	70
Cutoff frequency (GHz)	60
Time delay (ns/m)	4.7
Max. operating Voltage (kVrms)	2,000

Mechanical and Environmental Characteristics:

Items	Data
Min. bending radius static (mm)	6
Min. bending radius repeated (mm)	2
Operating temp. (°C)	-65 to +150
Weight (kg/km)	16

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp^{PRO}

Coaxial Cable RG405

multicomp PRO

Attenuation @ 20°C and Sea Level, Power:

Frequency (GHz)	Attenuation (dB/m)	Power (Watts CW)
0.5	0.49	338
1	0.72	219
2	1.07	142
3	1.34	110
5	1.80	80
10	2.67	52
18	3.73	36

Part Number Table

Description	Part Number
RG 405/U Tinned 50Ω Semi Flexible Coaxial Cable	PP000664

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp PRO