

FO patch cable - FOC-LC:PA-LC:PA-OM1:D01/3 - 1111843

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Your advantages

- Glass fiber optical, 8-shaped FO cable jumper
- Made of halogen-free flame retardant material, RoHS compliant



Key Commercial Data

Packing unit	1
GTIN	4 063151 032272
GTIN	4063151032272
Custom tariff number	85447000

Technical data

Dimensions

Length of cable	3.00 m	
Ambient conditions		
Ambient temperature (storage/transport)	-20 °C 60 °C	
General		
Insertion/withdrawal cycles	≥ 500	
Material		
Flammability rating according to UL 94	VO	
Cable		
Cable type	Multimode fiberglass	
Cable abbreviation	I-V(ZN)H	

Cable type	Multimode fiberglass
Cable abbreviation	I-V(ZN)H
Cable structure	Figure 8 cable



FO patch cable - FOC-LC:PA-LC:PA-OM1:D01/3 - 1111843

Technical data

Cable

External sheath, color	orange
Cable weight	5.30 kg/km
Outer sheath, material	LSZH
Halogen-free	According to IEC 60754-2
Resistance to oil	Not resistant to oil, gasoline, acids, and lyes
Concentration of fumes	in accordance with IEC 61034

Standards and Regulations

Concentration of fumes	in accordance with IEC 61034
Resistance to oil	Not resistant to oil, gasoline, acids, and lyes
Halogen-free	According to IEC 60754-2
Behavior in fire	No corrosive or toxic fumes
Flammability rating according to UL 94	V0

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50 years
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 8.0	27061801
eCl@ss 9.0	27061003

ETIM

ETIM 5.0	EC001578

Phoenix Contact 2020 © - all rights reserved http://www.phoenixcontact.com