Technical Data Sheet



PRODUCT DESCRIPTION: Silicone Oil Aerosol	DATE: 02/99
PRODUCT CODE: OSL400	PAGES: 1

PRODUCT DESCRIPTION

Electrolube's Silicone Oil Aerosol is a high quality multi-purpose mechanical lubricant. The **Silicone Oil Aerosol** is 100% Ozone Friendly.

PRODUCT USE

For all general and light duty mechanical lubrication purposes. One brief spray of **OSL** gives long term lubrication on line printers, keyboards, platens, bearings etc. **Silicone Oil Aerosol** may also be used as a release agent in moulding and casting operations. May be used both at work and home. Do not use near electrical contacts or motor brushes. Product contains **flammable solvent** therefore do not spray onto live electrical equipment or other sources of ignition.

FEATURES

- High quality silicone spray.
- Excellent water repellency.
- Excellent electrical insulating compound and sealant.
- Excellent lubricant with good adhesion.
- * Available in aerosol form for quick, clean and efficient application.

TYPICAL PROPERTIES (of the deposited oil)

Colour: Colourless

Specific Gravity: 0.90

Flash Point: >250°C

Viscosity (at 20°C): 200cSt

Pour Point: <-45°C

PACKAGING ORDER CODE

400ml Aerosol (100% Ozone Friendly) OSL400

Copyright Electrolube 1999

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.