ASTA021NN00100235000 ACTIVE



TE Internal #: ASA021N00100235000

Standard Circular Connectors, Cable-to-Cable, 12 Position, Signal, Cable Mount (Free-Hanging), Electrodeposited Nickel, Zinc Alloy,

PBT GF

View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors











Connector System: Cable-to-Cable

Number of Positions: 12

Sealable: No

Circuit Application: Signal

Connector Mounting Type: Cable Mount (Free-Hanging)

Features

Product Type Features

Froduct Type reatures	
Product Type	Connector
Connector System	Cable-to-Cable
Sealable	No
Circular Connector Type	Plug
Shell Type	Metal
Configuration Features	
Number of Positions	12
Number of Signal Positions	12
Electrical Characteristics	
Operating Voltage	160 VAC
Body Features	
Environmental Protection	IP67
Shell Plating Material	Electrodeposited Nickel

Zinc Alloy

Shell Base Material



Circular Connector Insulation	Material Type	PBT GF
	Triaterial Type	10101

Mechanical Attachment

Mating Retention Type	Screw
Panel Mount Feature Type	Screw Mount
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Circular Connector Shell Size	23
Alignment Keyed	Uncoded

Dimensions

Cable Diameter Range	5.5 – 10.5 mm[.22 – .41 in]
ada ta Brannatar Kanga	0.0 10.0 11.11[.22 . 11 11.]

Usage Conditions

Operating Temperature Range -20 – 1	130 °C[-4 – 266 °F]
-------------------------------------	---------------------

Operation/Application

Durability Rating	500 Cycles
Circuit Application	Signal
Shielded	Yes

Industry Standards

UL Flammability Rating	UL 94V-0
Approved Standards	UL

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUN 2020 (209) Candidate List Declared Against: JUN 2020 (209) SVHC > Threshold: Pb (3.5% in Component) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts



623 RECEPTACLE ANGLED ROTATABLE

TE Part # C0-0235-000-000 DIGITAL CRIMPING TOOL, SMALL TE Part # C0-0101-000-000 CRIMPING TOOL SMALL WITH **POSITIONER**

Customers Also Bought



D3200 FMLB REC STRAIN RELIEF KIT 4P RR



4P SS
















Standard Circular Connectors, Cable-to-Cable, 12 Position, Signal, Cable Mount (Free-Hanging), Electrodeposited Nickel, Zinc Alloy, PBT GF







Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_ASA021N00100235000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_ASA021N00100235000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_ASA021N00100235000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

ASA021N00100235000

English

Instruction Sheets

Instruction Sheet (non U.S.)

English