



Product Description


M



F


Worth knowing

screw termination

occupies 2 slots in the MCR frame

Suitable housing

EPIC® MCR 24

EPIC® MCR 16

EPIC® MCR 10

EPIC® MCR 6

EPIC® MC Modullösewerkzeug

EPIC® MCR 24

EPIC® MCR 16

EPIC® MCR 10

EPIC® MCR 6

Accessories
Technical Data
Rated voltage in V

1000 V

Rated current in A

82 A

Contact resistance

< 2 mOhm

Contacts

Copper alloy, hard silver plated

Numbers of contacts

2

Termination methods

 Screw connection: 10,0 - 25,0 mm²
Cycle of mechanical operation

100

Range of temperature

-40°C - +100°C, temporary up to +125°C

VDE-tested

VDE-REG.-No. 870

Pollution degree

3



Article List

| Part number | Part | Conductor cross-section in mm ² | Version | Contacts | Rated voltage in V | Rated current in A | Pieces / VPE |
|---|----------|--|---------|----------|--------------------|--------------------|--------------|
| Module: High Current 2 pole (occupies 2 slots in the MCR frame) | | | | | | | |
| 10344100 | MCS-HC 2 | 10 - 25 | male | 2 | 1000 | 82 | 5 |
| 10345100 | MCB-HC 2 | 10 - 25 | female | 2 | 1000 | 82 | 5 |