

871/1 TORQ-SET® Mplus Bits, 25 mm



Application:
For TORQ-SET®-screws
Drive: 1/4"-hexagon,
DIN 3126-C 6,3, ISO 1173

Tip: TORQ-SET® Mplus
similar ISO 7994, professional
quality

Code	mm	inch	mm		
066618	0	25	1"	4,7	10
066619	1	25	1"	4,7	10
066620	2	25	1"	4,7	10
066622	3	25	1"	4,7	10
066624	4	25	1"	4,7	10
066626	5	25	1"	4,7	10
066628	6	25	1"	4,7	10
066630	8	25	1"	6,0	10
066632	10	25	1"	6,0	10
066633	1/4"	25	1"	-	10

871/1 TORQ-SET® Mplus Bits, 32 mm



Application:
For TORQ-SET®-screws
Drive: 1/4"-hexagon,
DIN 3126-C 6,3, ISO 1173

Tip: TORQ-SET® Mplus
similar ISO 7994, professional
quality

Code	mm	inch	mm		
066634	1/4"	32	1 1/4"	11,0	10
066635	5/16"	32	1 1/4"	11,0	10

875/1 TRI-WING® Bits, 25 mm



Application:
For TRI-WING®-screws
Drive: 1/4"-hexagon,

DIN 3126-C 6,3, ISO 1173
Tip: TRI-WING®,
professional quality

Code	mm	inch	mm		
066758	0	25	1"	4,7	10
066760	1	25	1"	4,7	10
066762	2	25	1"	4,7	10
066764	3	25	1"	4,7	10
066766	4	25	1"	6,2	10
066768	5	25	1"	6,2	10

875/1 TRI-WING® Bits, 32 mm



Application:
For TRI-WING®-screws
Drive: 1/4"-hexagon,

DIN 3126-C 6,3, ISO 1173
Tip: TRI-WING®,
professional quality

Code	mm	inch	mm		
066770	6	32	1 1/4"	11,0	10
066772	7	32	1 1/4"	11,0	10
066774	8	32	1 1/4"	12,5	10



Information about TRI-WING® is provided on page 95.
Which Wera tool for which screw? See pages 190-193.

TORQ-SET® and TRI-WING® = reg. Trademarks of Phillips Screw Company.