MTO-215E2/120,

shown smaller than actual size.

LIGHTWEIGHT OIL IMMERSION HEATER

With 2 Element Design—2 NPT Steel Screw Plug

MTO-2 Series Starts at



- Rugged Steel Sheath for Use with Lightweight Oils
- ✓ 1.5 to 6 kW
- ✓ 120, 208, 240 or 480V;
 1 Phase
- ✓ General Purpose¹ NEMA-1 Rated and UL Listed Enclosure or Moisture Resistant/ Explosion Enclosure²

Note: The immersion heater should be used with an approved temperature control device to assure safe operation. See Temperature Section for our selection of process controllers.

SPECIFICATIONS

Wattage: 1.5 to 6 kW

Power: 120, 208, 240 or 480V; 1 phase

Watt Density: 23 to 26 W/in² Sheath: 1.2 cm (0.475") diameter Screw Plug: 2 NPT steel

Enclosure: E1 general purpose¹, NEMA-1 rated, or type E2 moisture resistant/explosion resistant enclosure.²

E1 Dimensions: cm (in) E1 Dimensions: cm (in) (4-13/16) 5 (2) Cold (Ref.) → 5.7 (2-1/4) 10.2 Min. Hole (4) Size Thermowell (2) 1.2 (0.475") Dia. Elements 3/4 NPT Conduit Opening E2 Dimensions: cm (in) 5 (2) Cold (Ref) — (2-1/4) Min. 8.6 (3-3/8) 13.2 (5-3/16) Nom (2) 1.2 (0.475) Dia. Ele (2) 3/4 NPT duit Opening **CAUTION AND WARNING!** Fire and electrical shock may result if products are used improperly or installed or used by non-qualified MTO-215A/120. personnel. See inside back cover

MOST POPULAR MODELS HIGHLIGHTED!

shown smaller than actual size.

To Order (Specify Model Number) E1 General Purpose Enclosure¹ E2 Explos. /Moist Res. Encl.2 Wt. Wt. No. Htg. Dim. B kW W/in² Model No. kg (lb) Model No. kg (lb) Elem. cm (in) MTO-215A/* MTO-215E2/* 2 30 (11¾) 1 (3) 3 (6) 1.5 24 2 24 2 45 (17¾) MTO-220A/* 2(4)MTO-220E2/* 3 (7) 2.5 26 2 9 (19%) MTO-225A/* 2(4)MTO-225E2/* 3(7)3 23 2 63 (24%) MTO-230A/* 2 (4) MTO-230E2/* 3(7)4 83 (323%) MTO-240A/* MTO-240E2/* 23 2 3(6)4 (8) 5 23 2 102 (40 1/4) MTO-250A/* MTO-250E2/* 3(7)4 (8)

for additional warning.

/*Designate voltage, i.e., insert "120" for 120 Vac, "208" for 208 Vac, "240" for 240 Vac, or "480" for 480 Vac.

Ordering Example: MTO-215A/240, 1.5 kW heater powered by 240 Vac.

Caution: Explosion resistant type E2 construction refers to heater design features which provide explosion resisting containment of electrical wiring according to National Electric Code. Abnormal application or use of heaters which in excessive temperatures can create hazardous conditions which can lead to fire

^{//*} Designate voltage, ie., insert "208" for 208 Vac, "240" for 240 Vac, or "480" for 480 Vac.

¹ Heaters with General Purpose Enclosures are UL recognized and CSA Certified.

² Heaters with Moisture Resistant/Explosion Resistant Enclosures are CSA NRTL/C Certified.

Your One-Stop Source for Process Measurement and Control!

One Omega Drive | Stamford, CT 06907 | 1-888-TC-OMEGA (1-888-826-6342) | info@omega.com

www.omega.com



UNITED STATES

www.omega.com 1-800-TC-OMEGA Stamford, CT.

CANADA

www.omega.ca Laval(Quebec) 1-800-TC-OMEGA

GERMANY

www.omega.de Deckenpfronn, Germany 0800-8266342

UNITED KINGDOM

www. omega.co.uk Manchester, England 0800-488-488

FRANCE

www.omega.fr Guyancourt, France 088-466-342

CZECH REPUBLIC

www.omegaeng.cz Karviná, Czech Republic 596-311-899

BENELUX

www.omega.nl Amstelveen, NL 0800-099-33-44



More than 100,000 Products Available!

Temperature

Calibrators, Connectors, General Test and Measurement Instruments, Glass Bulb Thermometers, Handheld Instruments for Temperature Measurement, Ice Point References, Indicating Labels, Crayons, Cements and Lacquers, Infrared Temperature Measurement Instruments, Recorders Relative Humidity Measurement Instruments, RTD Probes, Elements and Assemblies, Temperature & Process Meters, Timers and Counters, Temperature and Process Controllers and Power Switching Devices, Thermistor Elements, Probes and Assemblies, Thermocouples Thermowells and Head and Well Assemblies, Transmitters, Wire

Flow and Level

Air Velocity Indicators, Doppler Flowmeters, Level Measurement, Magnetic Flowmeters, Mass Flowmeters, Pitot Tubes, Pumps, Rotameters, Turbine and Paddle Wheel Flowmeters, Ultrasonic Flowmeters, Valves, Variable Area Flowmeters, Vortex Shedding Flowmeters

pH and Conductivity

Conductivity Instrumentation, Dissolved Oxygen Instrumentation, Environmental Instrumentation, pH Electrodes and Instruments, Water and Soil Analysis Instrumentation

Data Acquisition

Auto-Dialers and Alarm Monitoring Systems, Communication Products and Converters, Data Acquisition and Analysis Software, Data Loggers Plug-in Cards, Signal Conditioners, USB, RS232, RS485 and Parallel Port Data Acquisition Systems, Wireless Transmitters and Receivers

• Pressure, Strain and Force

Displacement Transducers, Dynamic Measurement Force Sensors, Instrumentation for Pressure and Strain Measurements, Load Cells, Pressure Gauges, Pressure Reference Section, Pressure Switches, Pressure Transducers, Proximity Transducers, Regulators, Strain Gages, Torque Transducers, Valves

Heaters

Band Heaters, Cartridge Heaters, Circulation Heaters, Comfort Heaters, Controllers, Meters and Switching Devices, Flexible Heaters, General Test and Measurement Instruments, Heater Hook-up Wire, Heating Cable Systems, Immersion Heaters, Process Air and Duct, Heaters, Radiant Heaters, Strip Heaters, Tubular Heaters