



DisplayMount™ Adhesive

Product Data Sheet

Updated : February 1997
Supersedes : February 1996

Product Description

Improved 3M DisplayMount™ is a multi purpose adhesive that is specially designed for exhibition, studio and theatre sets, display work and many other applications where heavy duty adhesive is needed.

It is ideal for bonding most porous and non porous materials including many plastics, fabrics, metal foils, paper, board, carpeting and rubber.

The new controlled spray pattern greatly reduces adhesive mist.

Physical Properties

Not for specification purposes

Solvent	Petroleum Distillate / Cyclohexane	
Flash Point	-46°C	
Propellant	Hydrocarbon	
Contents	400 ml (279g)	
Spray Pattern	Particle	
Colour	Clear/Pale Cream	
Shelf Life	12 months from date of receipt by customer when stored in the original carton at 21°C (70°F) & 50 % Relative Humidity	

Additional Product Information

Does not contribute to ozone depletion.

Coverage:

Approximately 10m² (120 square feet) per container, depending on porosity of substrate.

Storage Conditions Cool dry place. Best results are obtained when material is stored and applied at room temperature 16 to 27°C. Storage temperature must not exceed 49°C.

Directions for Use

<p>Ensure all surfaces to be bonded are clean, dry and free from dust, oil and grease before application of adhesive.</p> <p>Ensure that the nozzle points away from all persons and towards the surface to be sprayed. Turn the spray tip to select the desired spray width.</p> <p>Shake can well before using, 5-10 seconds should be sufficient.</p> <p>Hold the container 15 to 20 cms from the surface and apply evenly to cover the entire area.</p>	<p>To bond porous materials (such as paper, board and fabric) apply to one surface only and place in position while the adhesive is still wet. For non porous materials (such as metal foils, plastics and film) spray adhesive onto both surfaces and let adhesive become aggressively tacky before bonding.</p> <p>To prevent nozzle from blocking, at the end of each day turn the can upside down and press the tip until spray is clear from adhesive, and wipe tip.</p>	<p>Clean Up: Spray nozzle or excess adhesive may be cleaned with white spirits.</p> <p>NOTE: When using solvents for clean up, it is essential that proper safety precautions are observed.</p>
---	---	---

Applications DisplayMount™ is extensively used for bonding lightweight boards, foams, plastics, fabric, paper and many other materials.

For bonding backcloths in studios and window dressing, and bonding polystyrene foam in exhibition displays and 3D lettering

Health and Safety Information For further information please contact our Product Responsibility / Toxicology Department in Bracknell on 01344 858000.

3M and DisplayMount are trademarks of the 3M Company.

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.



Tapes & Adhesives

© 3M United Kingdom PLC 1996

3M United Kingdom PLC
3M House,
28 Great Jackson Street,
Manchester,
M15 4PA

Product Information :
Tel 0870 60 800 50
Fax 0870 60 700 99

3M Ireland
3M House, Adelphi Centre,
Upper Georges Street,
Dun Laoghaire, Co. Dublin,
Ireland

Customer Service :
Tel (01) 280 3555
Fax (01) 280 3509