

PRESSURE SWITCH ACCESSORIES

70A

AUDIBLE ALARM

OMEGA's Model 70A audible alarms are the latest development in solid sound production. When 120 Vac is applied to them, a piezoelectric transducer operates

as a solid state oscillator, resulting in a loud alarm tone. A small, 29 mm (1.13") diameter hole is required for panel mounting.

To Order	
MODEL NO.	TONE TYPE
70A-1	Continuous tone
70A-2	Fast pulse tone
70A-3	Slow pulse tone
70A-4	Warble tone



70A-4, shown larger than actual size.

SSR330

HIGH-RELIABILITY SOLID STATE RELAYS

Solid state relays are used for switching large loads and, in conjunction with pressure switches, they extend the power rating of the switch.

To Order		
MODEL NO.	CONTROL SIGNAL	MAX AC OUTPUT
SSR330AC10	AC	10 A
SSR330AC25	Control Signal	25 A
SSR330AC50	(100 to 280 Vac)	50 A
SSR330DC10	DC	10 A
SSR330DC25	Control Signal	25 A
SSR330DC50	(4 to 32 Vdc)	50 A
FHS-2	Finned heat sink	



SSR330DC10 with cover, shown smaller than actual size.

TD Series



DELAY RELAYS

Delay relays are used to eliminate false pressure transients from sounding high alarms (TD-69). The TD-73 is used to prevent furnaces and compressors from quick restarts.

To Order		
MODEL NO.	ADJUSTABLE TIME DELAY	TYPE
TD-69	6 seconds to 8 minutes	Delay-on-make
TD-73	6 seconds to 5 minutes	Delay-on-break