

Round LED

5mm, Yellow Green

multicomp^{PRO}

RoHS
Compliant



Features

- 5mm Rounded LED Lamps
- Low power consumption
- Excellent product quality and reliability
- Lead-free device

Applications

- Electronic signs and signals
- Bright ambient lighting conditions
- Backlight.
- General purpose indicators

Device Selection Guide

Part No.	Chip		Lens color
MP008541	Material	Emitted color	Water Clear
	GaP	Yellow Green	

Absolute Maximum Ratings: (T_A = 25°C)

Parameter	Symbol	Value	Unit
Power Dissipation	P _D	50	mW
Forward Current	I _F	30	mA
Peak Forward Current ^{*1}	I _{FP}	100	mA
Reverse Voltage	V _R	5	V
Operating Temperature	T _{OPR}	-40 to +85 ▲	°C
Storage Temperature	T _{STG}	-40 to +85	°C
Soldering Temperature ^{*2}	T _{SOI}	260°C For 5 Seconds Δ	

Notes:

*1: Pulse width ≤ 0.1ms, Duty cycle ≤ 1/10

*2: Δ At the position of 3mm below package base.

*3: ▲ Please refer to the curve of forward current vs. temperature

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp^{PRO}

Round LED

5mm, Yellow Green

multicomp PRO


Electrical / Optical Characteristics at T _A = 25°C						
Parameter	Symbol	Min.	Typ.	Max	Unit	Test Conditions
Forward Voltage	V _F	1.8	2.2	2.6	V	IF=20mA
Reverse Current	I _R	—	—	10	μA	VR=5V
Dominant Wavelength	λ _d	565	570	575	nm	IF=20mA
Peak Wavelength	λ _P	—	565	—	nm	
Spectral line Half-width	Δλ	—	30	—	nm	
Luminous Intensity	I _v	150	300	600	mcd	
Power Angle	2θ _{1/2}	—	15	—	Deg.	

Remarks:

If special sorting is required (e.g. binning based on forward voltage, luminous intensity, or dominant wavelength), the typical accuracy of the sorting process is as follows:

1. Dominant Wavelength: +/-1nm
2. Chromatic Coordinates: +/-0.01
3. Luminous Intensity: +/-15%

Dimensions



Dimensions : Millimetres

Notes:

1. All dimensions are in millimeters.
2. Tolerance is ±0.25 unless otherwise noted.
3. Lead spacing is measured where the leads emerge from the package.
4. Specifications are subject to change without notice.
5. The design and working current for LED is not less than 2mA.

Newark.com/multicomp-pro
 Farnell.com/multicomp-pro
 Element14.com/multicomp-pro

multicomp PRO

Round LED

5mm, Yellow Green

multicomp PRO

VF Rank

Rank	VF(V)		Condition
	Min	Max	
A2B1	1.8	2	IF=20mA
B2C1	2	2.2	
C2D1	2.2	2.4	
D2E1	2.4	2.6	

Tolerance : $\pm 0.1V$

λD Rank

Rank	λD (nm)		Condition
	Min	Max	
K6K7	565	567	IF=20mA
K8K9	567	569	
KAKB	569	571	
KCKD	571	573	
KEKF	573	575	

Tolerance : $\pm 0.1nm$

IV Rank


Rank	IV(mcd)		Condition
	Min	Max	
J	150	250	IF=20mA
K	250	400	
L	400	600	

Tolerance : $\pm 15\%$


Round LED

5mm, Yellow Green


Typical Electrical/Optical Characteristics Curves




FORWARD CURRENT Vs.
FORWARD VOLTAGE



LUMINOUS INTENSITY Vs.
FORWARD CURRENT



FORWARD CURRENT
DERATING CURVE





LUMINOUS INTENSITY Vs.
AMBIENT TEMPERATURE

Round LED

5mm, Yellow Green

multicomp PRO



Part Number Table

Description	Part Number
Round LED, Yellow Green, 565nm, 15°, 300mcd, Through hole	MP008541

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
 Farnell.com/multicomp-pro
 Element14.com/multicomp-pro

multicomp PRO