

XLR CHASSIS CONNECTORS

4 PIN E SERIES - HORIZONTAL PCB MOUNT

Locking horizontal PCB Mount 4 pin chassis connector with plastic body perfect for use in DC power, aviation, communications, and other AV applications.

Other Available Mounting Option: Vertical PCB Mount



PRODUCT

Gender: Male (IO-XLR4-M-EH)

Female (IO-XLR4-F-EH)

Contacts: 4

ELECTRICAL

Capacitance Between Contacts: ≤ 3.3 pF

Capacitance Between Contact and Ground: ≤ 2.9 pF

Contact Resistance: $< 6 \text{ m}\Omega$

Insulation Resistance: ≥ 5000 MΩ

Dielectric Strength: 1500V @ 60s

Current Rating: 3 A / 50 V AC

Grounding: Separate ground pin. Grounds to shell of

mating connector and panel

ENVIRONMENTAL

Standard Compliance: IEC 61076-2-103

UL Flammability Rating: UL94 V-0

Temperature Range: -40° C $\sim +70^{\circ}$ C $(-40^{\circ}$ F $\sim +158^{\circ}$ F)





IO-XLR4-M-EH

IO-XLR4-F-EH

MECHANICAL

Lifetime: > 1000 Mating Cycles

Wiring: Horizontal PCB Mount

Locking Device: Latch Lock

Mounting Direction: Rear

Solderability: Complies with IEC

60068-2-20

MATERIAL

Contacts: Brass

Contact Plating: .05µm Au

Ground Terminal: Brass

Ground Terminal Finish: Nickel

Shell: PA

Shell Finish: Black

Push Button: Stainless Steel

Push Button Finish: Nickel


Latch: Stainless Steel

Latch Finish: Nickel

DRAWINGS

IO-XLR4-F-EH


IO-XLR4-M-EH



FEATURES & APPLICATIONS

E Series XLR chassis connectors offer the most cost-effective solution for design-in applications where the termination method is to a printed circuit board. The small footprint makes this our XLR receptacle with the highest packing density available. These connectors feature a compact all plastic housing with precision machined, one piece, gold plated contacts to help prolong the useful life of the connectors. They also come with a separate nickel plated ground pin that grounds the connector to the panel. The compact form factor of these connectors makes them perfect for situations where space saving is a priority or space for a connector is limited.

Panel Cutout



Available in 3, 4 or 5 pin, Male or Female variations with options for vertical or horizontal PCB mounting.

PART NUMBER BREAKDOWN:

IO-XLR4-M-EH
Series Identifier
IO-XLR4-M-EH
Number of Pins
IO-XLR4-M-EH
Gender
IO-XLR4-M-EH
Series Identifier
IO-XLR4-M-EH
H = Horizontal PCB Mount
V = Vertical PCB Mount

STANDARDS & CLASSIFICATIONS

