2.5mm Jack Socket 4 Pole

pro-**signal**



Specifications


No. of Contacts Gender Pin Diameter Contact Resistance Insulation Resistance Dielectric Strength : 4 Contacts

- : Jack
- : 2.5mm
- : 50mΩ Max.
- . 3011122 IVIA
- : 100MΩ Min. at 500V DC : 500V AC for one Minute




CIRCUIT

- CONTACT C - CONTACT B - CONTACT A - CONTACT D









No.	Part Name	Material	Finish	Qty
1	Housing	PA	-	
2	Sleeve	BSBM	Ni	
3	Contact A	PBS t=0.25	Ni	
4	Contact B	PBS t=0.25	Au	1
5	Contact C	PBS t=0.25	Ni	
6	Contact D	BSR t=0.3	Ni	
7	Hex Nut	Steel	Ni	

Part Number Table

	Description	Part Number	
ensions : Millimetres	2.5mm Jack Socket, 4 Pole	PSG08265	

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-SIGNAL is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands Farnell.com/exclusive-brands Element14.com/exclusive-brands

