90 Deg. 3.5mm Jack Plug 4 Pole

pro-signal



Diagram


c

1 4

0

Specifications

- No. of Contacts Gender Pin Diameter Contact Resistance Insulation Resistance Dielectric Strength
- : 4 Contacts
- : Plug
- : 3.5mm
- : 50mΩ Max.
- : 100MΩ Min. at 500V DC
- : 500V AC for one Minute



No.	Part Name	Material	Finish	Qty
1	Contact A	Brass	Ni	
2	Contact B	Ebonite	Ni	
3	Contact C	PVC	Ni	
4	Contact D	Brass	Ni	
5	Insulator A	PF	-	1
6	Insulator B	Brass	-	
7	Frame	Steel	Ni	
8	CAP	PP	-	
9	Cable Protector	PVC	-	

Part Number Table

Description	Part Number	
90 Degree 3.5mm Jack Plug, 4 Pole	PSG08270	

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage ersulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-SIGNAL is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands Farnell.com/exclusive-brands Element14.com/exclusive-brands

Dimensions : Millimetres

