


For mating dimensions see MIL-DTL-38999 Series III

Reference MIL-STD-1560 for insert arrangement details. For non-MS arrangements consult Amphenol.



For rear shell features and accessories see MIL-DTL-38999 Series III

NOTE:

- DRAWING NOT TO SCALE
- DIMENSIONS SUBJECT TO CHANGE
- DIMENSIONS ARE IN INCHES [MM]

PROPERTY OF AMPHENOL AEROSPACE. ALL RIGHTS RESERVED.

Meets applicable requirements of MIL-DTL-38999
 Base Material: Aluminum
 Plating: AP-93

AMPHENOL CORPORATION

40-60 DELAWARE AVENUE
 SIDNEY, N.Y. 13838


PLUG
 Electrical Connector
 TVS06

U

SIZE	CAGE CODE	CODED NUMBER	REV
C	77820	TVS06DS-17-35S	X1

SHEET 1 OF 1

Insert Arrangement



No. of Contacts	55
Contact Size	22D
Wire Size	28, 26, 24, 22

Shell Size	17
Arrangement	35
Service Rating	M
Test Current	5 AMPS

NOTE:
 -DRAWING NOT TO SCALE
 -DIMENSIONS SUBJECT TO CHANGE
 -DIMENSIONS ARE IN INCHES [MM]

PROPERTY OF AMPHENOL AEROSPACE. ALL RIGHTS RESERVED.

AMPHENOL CORPORATION <small>40-60 DELAWARE AVENUE SIDNEY, N.Y. 13838</small>			
PLUG Electrical Connector TVS06			U
<small>SIZE</small> C	<small>CAGE CODE</small> 77820	<small>CODED NUMBER</small> TVS06DS-17-35S	<small>REV</small> X1
SHEET 1 OF 1			