

Thermistor Meters

Series 860



No Points



OMEGACARESM extended warranty program is available for models shown on this page. Ask your sales representative for full details when placing an order. OMEGACARESM covers parts, labor and equivalent loaners

- ✓ Comes with Certificate Stating NIST-Traceability
- ✓ Computable with All Series "400" Thermistor Sensors and Probes
- ✓ Rugged
- ✓ 0.1° Resolution
- ✓ Economical and Accurate

Specifications

Sensor: OMEGA[®] Series 400 Thermistor (2252 Ω @ 25°C); or thermistors with 44004 element

Accuracy: Includes repeatability, temperature coefficient (18 to 28°C ambient), times stability (1 year) and linearization conformity errors; excludes probe errors

Repeatability: 0.1°C (0.2°F) typical for 1 week at constant ambient temperature

Temperature Coefficient: 18 to 28°C (64 to 82°F); included in accuracy specification; less than 18°C (64°F) or greater than 28°C (82°F) less than ± (0.06% rdg + 0.01°C)/°C

Linearization: Ratiometric dual slope A/D with continuous linearization

Mating Connection: ¼" phone jack; model PPM-2

Display: 3½ digit LCD, 13 mm (0.5") height; polarity, decimal point, open sensor and overrange indication

Reading Rate: 1.5 per second

Battery Life: 350 hours typical, with 9 V alkaline battery (included)

Battery Indicator: Display reads "LO BAT" when less than 10% of life remains

Environmental Limits:

Operating: -10 to 50°C (14 to 122°F), less than 80% RH, up to 35°C

Storage: -35 to 60°C (-31 to 140°F), less than 90% RH, up to 35°C

Maximum Common Mode Voltage: 42 V peak

Dimensions: 160 x 69 x 31 mm (6.3 H x 2.7 W x 1.2" D)

Net Weight: 210 g (7.5 oz)

The 865F and 866C thermistor thermometers offer exceptional value combining thermistor accuracy, heavy duty construction and probe interchangeability.

Sensor sold separately. See OMEGA's complete line of thermistor probes and handles online.

Phone plug connector provided FREE with each unit.

865F shown smaller than actual size.



To Order				
Model No.	Setting	Range	Resolution	Accuracy
865F	200°F	-70.0 to -40.1°F	0.1°F	±(0.3%rdg +1.0°F)
	300°F	-40.0 to 199.9°F	0.1°F	±(0.3%rdg +0.5°F)
		-70 to 300°F	1°F	±(0.3%rdg +1°F)
866C	150°C	-55.0 to -40.1°C	0.1°C	±(0.3%rdg +0.6°C)
		-40.0 to 150.0°C	0.1°C	±(0.3%rdg +0.3°C)
Accessories				
Model No.	Description			
CAL-3-HH	NIST-traceable calibration with points			
SC-800	Soft carrying case			
PPM-2	Extra mating phone plug			
MN1604	9 V alkaline battery			
EXPP-2CU-24S-50	Extension wire for Series 400 thermistors, 24 gage polyvinyl insulation, 15 m (50')			
OT-201-1/2	½ oz jar of high thermal conductivity paste for fast surface measurements			

Comes with battery, operator's manual, and phone plug (PPM-2).

Ordering Example: 865F, thermistor thermometer, in fahrenheit readout. OCW-3, OMEGACARESM extends standard 1-year warranty to a total of 4 years.