Enclosed Changeover Switch Multicomp





Features

- Under load operation
- Earth terminal included
- Captive ±terminal screws
- Pad lockable in OFF position (up to 3 padlocks)
- Lid interlocked with switch in position 1 and 2
- IP65 rating in all the enclosures
- Manufactured to IEC60947-3

Electrical Ratings (According to IEC 60947-3)

AC Rated thermal current Ith (40°C) : 32A : 690 Rated insulation voltage Ui (V) Rated impulse withstand voltage Uimp (kV) : 6

AC Rated operational current le (A)

Rated voltage Utilization category le 415V AC AC22A 32

Connection Capacity

Rigid cable (Cu) mm² : 2×6 Flexible cable (Cu) mm² : 2×4

Standards


IEC 60947-3

Approvals


CE, UL listed, Bureau Veritas

Dimensions

175mm × 151mm × 95mm



Electrical Drawing



Part Number Table

Description	Part Number
2 Pole Changeover Switch, 32A	MCLBC322P

Dimensions: Millimetres

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

