### 1SNK531020R0000 ✓ ACTIVE

## ENTRELEC | ENTRELEC SNK

TE Internal #: 1SNK531020R0000

Modular Terminal Blocks, Feed-Through, Screw Clamp Terminal Block, Blue, Product Spacing 1.22 in [31 mm], 2 Position, DIN Rail,

ENTRELEC SNK


View on TE.com >



Connectors > Terminal Blocks & Strips > Modular Terminal Blocks









Screw Clamp Terminal Block

1000 V

12000 V

1000 V

310 A

9.9 W

3820 V



Block Function: Feed-Through

Modular Terminal Block Product Type: Screw Clamp Terminal Block

Operating Voltage Rating (UL & CSA) (Max) - Main Circuit

Impulse Withstanding Voltage Rating (IEC)

Voltage Rating (CSA)

Current Rating (CSA)

Dielectric Test Voltage

Power Loss

Rated Cross Section: **350 kcmil**Primary Product Color: **Blue** 

Modular Terminal Block Product Type

### **Features**

### **Product Type Features**

Configuration Features	
Gauge Type	B14
Number of Levels	1
Number of Poles	1
Number of Circuits	1
Block Function	Feed-Through
Number of Positions	2
Electrical Characteristics	



Short-Time Withstanding Current Rating @ 1s	18000 A
Voltage Rating (IEC)	1000 V
Current Rating (UL)	310 A
Current Rating (IEC)	309 A
Body Features	
Product Weight	318 g[12.52 oz]
Primary Product Color	Blue
Mechanical Attachment	
DIN Rail Mounting Type	TH35-15, TH35-7.5
Tightening Torque	177 in-lbs
Connector Mounting Type	DIN Rail
Housing Features	
Housing Material	Polyamide
Dimensions	
Main Circuit Capacity - 1 Rigid Stranded Conductor per Screw Clamp	35 – 185 mm²
Main Circuit Capacity - 1 Flexible Conductor per Screw Clamp	50 – 150 mm²
Wire Stripping Length	40 mm[1.575 in]
Main Circuit Capacity - 2 Flexible Conductors per Screw Clamp	$.5 - 10 \text{ mm}^2$
Main Circuit Capacity - 2 Rigid Stranded Conductors per Screw Clamp	.5 – 16 mm²
Tool Size	8 mm[.315 in]
Product Depth	107 mm
Product Height	119.4 mm
Rated Cross Section	350 kcmil
Product Spacing	31 mm[1.22 in]
Usage Conditions	
Storage Temperature Range	-55 – 110 °C[-67 – 230 °F]
Installation Temperature Range	-5 - 40 °C[23 - 104 °F]
Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]
Industry Standards	
UL Flammability Rating	UL 94V-0



### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**













































## Also in the Series | ENTRELEC SNK





Accessories(67)



## Customers Also Bought





TE Part #1SNA190008R0700 D120/42.AF



















### **Documents**

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1SNK531020R0000\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1SNK531020R0000\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1SNK531020R0000\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

### Datasheets & Catalog Pages

**ENTRELEC Terminal Block - Master Catalog** 

English

ZS150-BL

English

### 1SNK531020R0000

Modular Terminal Blocks, Feed-Through, Screw Clamp Terminal Block, Blue, Product Spacing 1.22 in [31 mm], 2 Position, DIN Rail, ENTRELEC SNK



#### SNK SERIES TERMINAL BLOCKS

English

Agency Approvals
CE Declaration of Conformity

English