

Floudel Sealer Data Silee

Note: This datasheet may be out of date.

Please download the latest datasheet of GRM155R60G106ME47# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=GRM155R60G106ME47%23

"#" indicates a package specification code.

# GRM155R60G106ME47D













For only mobile devices

< List of part numbers with package codes > GRM155R60G106ME47D GRM155R60G106ME47J



## Appearance & Shape







### References

| Packaging | Specifications   | Standard |
|-----------|------------------|----------|
|           |                  | Packing  |
|           |                  | Quantity |
| D         | 180mm Paper Tape | 10000    |
| J         | 330mm Paper Tape | 40000    |

| Mass (typ.) |       |  |
|-------------|-------|--|
| 1 piece     | 3.1mg |  |
| φ180mm Reel | 149g  |  |



### **Notices**

Only for mobile devices. Measure capacitance after heat treatment

1 of 2

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





### Product Search Data Sneet

GRM155R60G106ME47D

Note: This datasheet may be out of date.

Please download the latest datasheet of GRM155R60G106ME47# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=GRM155R60G106ME47%23

"#" indicates a package specification code.



# **Specifications**

| Length   | 1.0±0.2mm      |
|--|----------------|
| Width  | 0.5±0.2mm      |
| Thickness  | 0.5+0/-0.1mm   |
| Capacitance                                      | 10μF ±20%      |
| Distance between external terminals g            | 0.3mm min.     |
| External terminal size e                         | 0.15 to 0.35mm |
| Operating Temperature<br>Range                   | -55°C to 85°C  |
| Rated Voltage                                    | 4Vdc           |
| Size code in inch(mm)                            | 0402 (1005M)   |
| Capacitance change rate                          | ±15.0%         |
| Temperature characteristics (complied standard)  | X5R(EIA)       |
| Temperature range of temperature characteristics | -55°C to 85°C  |

2 of 2

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

