

Coaxial Cable Connector 24_BNO-0-4-1/133_N

Description

Straight bulkhead cable feed through

Interface standards
IEC 60169-22



Technical Data

Electrical Data

| | |
|--------------------------|----------------------|
| Impedance | not defined Ω |
| Interface frequency max. | 0.2 GHz |

Mechanical Data

| | |
|----------------|-----------|
| Centre contact | soldered |
| Outer contact | crimped |
| Weight | 0.0202 kg |

Environmental Data

| | |
|--|------------------|
| Operating temperature | -50 °C to 125 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant |

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|-------------------------------------|-----------------------------------|
| Centre contact | Copper Beryllium / Brass | Gold Plating (Nickel underplated) |
| Outer contact | Brass | SUCOPLATE (R) Plating |
| Body | Brass | SUCOPLATE (R) Plating |
| Insulator | ETFE (Ethylene tetrafluoroethylene) | |
| Gasket | VMQ (Silicone rubber) | |
| Fastening nut | Brass | SUCOPLATE (R) Plating |
| Washer | Bronze | SUCOPLATE (R) Plating |
| Crimp ferrule | Copper | SUCOPLATE (R) Plating |

Related Documents

| | |
|----------------------|----------------|
| Outline drawing | DOU-00008925 |
| Catalogue drawing | DCA-00008927 |
| Assembly instruction | DOC-0000180938 |
| Mounting hole | DOU-00008751 |

Ordering Information

| | |
|----------------|---------------------|
| Single package | 24_BNO-0-4-1/133_NE |
|----------------|---------------------|

Additional Information

| | |
|-----------------|---------------------|
| Suitable cables | RG_108_A/U, K_05790 |
|-----------------|---------------------|