



# Jauch Battery Solutions

- Reliable energy for your application
- Standard cells and customized packs
- ESD protection
- Battery Certification Experts



RoHS compliant



Pb free



REACH  
compliant



Conflict  
Mineral free

## Product Safety Data Sheet

According Regulation (EC) No 1907/2006 (REACH) a safety data sheet must be provided for substances and preparations only. Batteries are “articles” and therefore not affected by the requirements of this Regulation.

Based on the definition of “article” in the Occupational Safety and Health Administration (OSHA) Hazard Communication Standard, 29 CFR Subpart 1910.1200, there is no requirement for a Material Safety Data Sheet (MSDS) for lithium primary cells. There is no release of toxic chemicals under normal conditions of use.

---

### Section I - Identification

---

Product Name: Lithium Metal (non-rechargeable) Battery

Model: ER Lithium Primary 3.6V cell

Chemical System: Lithium-Thionyl-Chloride (Li-SOCI<sub>2</sub>)

Recommended use : no restriction (see section VII Handling and Storage)

Manufacturer: Jauch Quartz GmbH  
In der Lache 24  
78056 Villingen-Schwenningen / Germany  
Tel: +49 7720 945 0  
www.jauch.com



# Jauch Battery Solutions

- Reliable energy for your application
- Standard cells and customized packs
- ESD protection
- Battery Certification Experts



RoHS compliant



Pb free



REACH compliant



Conflict Mineral free

## Section II – Hazard Identification

Batteries are articles and therefore exempted from the UN-GHS classification requirements. There are no GHS labelling requirements for articles. Other labelling requirements apply for batteries according to the EU Directive 2006/66 for batteries.

The chemicals mentioned in Section III are contained in a sealed can. Risk of exposure occurs only if the cell / battery is mechanically or electrically abused.

## Section III – Composition / Information on ingredients

The regulations for substances are not applicable, as cells or batteries are articles under the relevant definitions. The chemicals mentioned are contained in a sealed steel can. Risk of exposure occurs only if the cell / battery is mechanically or electrically abused. Conditions to avoid: cells or batteries may explode when placed in a fire, when exposed to excessive heat, when opened or during inappropriate use.

Hazardous substances contained in the article according to UN-GHS (for information purposes only):

Chemical Name	Molecular Formula	CAS No.	Weight(%)
Lithium	Li	7439-93-2	3.5~5.0
Carbon	C	1333-86-4	3~6
Tetrafluoroethylene	(C <sub>2</sub> F <sub>4</sub> ) <sub>n</sub>	9002-84-0	N/A
Thionyl Chloride	SOCl <sub>2</sub>	7719-09-7	40~45
Aluminum Chloride	AlCl <sub>3</sub>	7446-70-0	1-5
Lithium Chloride	LiCl	7447-41-8	N/A
Stainless Steel	N/A	N/A	N/A
Glass	Na <sub>2</sub> O.CaO.6SiO <sub>2</sub>	N/A	N/A
Nickel	Ni	7440-02-0	N/A

The UN GHS labelling information is not provided in this section as batteries are articles and therefore are exempted from the UN GHS labelling requirements. Other labelling requirements apply for batteries according to EU Directive 2006/66/EC.

## Section IV - First Aid Procedures

**None** unless internal material exposure.

### Skin contact:

Contents of an opened battery can cause irritation, wash immediately with soap and water. Remove contaminated clothing. If irritation persists, get medical help.



# Jauch Battery Solutions

- Reliable energy for your application
- Standard cells and customized packs
- ESD protection
- Battery Certification Experts



RoHS compliant



Pb free



REACH compliant



Conflict Mineral free

## Eye contact:

Contents of an opened battery can cause severe irritation, IMMEDIATELY FLUSH THOROUGHLY WITH COPIOUS AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION.

## Ingestion:

CALL MEDICAL PRACTITIONER IMMEDIATELY

## Inhalation:

Do not inhale leaked material. PROVIDE IMMEDIATELY FRESH AIR, IF IRRITATION PERSISTS, GET MEDICAL HELP.

---

## Section V - Fire Fighting Instructions

---

### 5.1 Fire and explosion hazard:

The battery can leak and/or spout vaporized or decomposed and combustible electrolyte fumes in case of exposure above 100°C resulting from inappropriate use or the environment. Cells or batteries may flame or leak potentially hazardous organic vapors if exposed to excessive heat or fire. Fire, excessive heat, or over voltage conditions may produce hazardous decomposition products. Damaged or opened cells or batteries can result in rapid heating and the release of flammable vapors. Vapors may be heavier than air and may travel along the ground or be moved by ventilation to an ignition source and flash backfire, excessive heat, or over voltage conditions may produce hazardous decomposition products. During water application, caution is advised as burning pieces of flammable particles may be ejected from the fire.

### 5.2 Extinguishing Media:

Suitable CO<sub>2</sub> or dry chemical extinguishers

Dry chemical or Foam extinguishers.

Special Fire Fighting Procedure: WEAR NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT.

Unusual Fire and Explosion Hazards: NONE SPECIFIED BY MANUFACTURER.

As with any fire, wear self-contained breathing apparatus to avoid inhalation of hazardous decomposition products.

---

## Section VI - Accidental Release

---

### General

Chemical contents are sealed in metal can. But if the battery is mechanically or electrically abused, contents may leak out. In such case, take action as showing below.

The preferred response is to leave the area and allow the batteries to cool and the vapours to dissipate.



# Jauch Battery Solutions

- Reliable energy for your application
- Standard cells and customized packs
- ESD protection
- Battery Certification Experts



RoHS compliant



Pb free



REACH  
compliant



Conflict  
Mineral free

## *Personal precautions*

Avoid skin and eye contact or inhalation of vapours. Temporary inhalation of odor and attaching of electrolyte to skin does not cause serious health hazard. Be sure the ventilation and washing out of electrolyte quickly.

## *Environmental precautions*

Collect all released material in a plastic lined metal container and remove spilled liquid with absorbent. Doing this, protect your skin and eyes with gloves and protection glasses. Avoid direct contact with internal components. Specific environmental precaution is not necessary.

---

## Section VII – Handling and Storage

---

When used correctly, Lithium-Metal Battery (Non-Rechargeable Single cell Battery) provides a safe and dependable source of power. However, if they are misused or abused, leakage, venting, or in extreme cases explosion and/or fire may result.

Make sure to observe amongst others, following warnings.

### Handling:

- Do not insert batteries in reverse. Observe the polarity markings on battery and equipment
- Do not short-circuit batteries
- Do not charge batteries
- Do not deform or disassemble batteries
- Do not incinerate or dispose batteries in fire
- Do not place battery on metal case, metal plate or antistatic material
- Do not mix batteries types or brands. In case of multi cell application, replace all batteries to new at once when replacing used batteries
- Do not heat batteries or exposure direct sunlight
- Do not weld or solder directly to batteries
- A battery with a damaged container should NOT be exposed to water
- Do not allow children to replace batteries without adult supervision
- Keep batteries out of the reach of children. In case of ingestion of a cell or battery, the person involved should seek medical assistance immediately
- Equipment intended for use by children should have battery compartments which are tamper-proof
- Do not encapsulate and/or modify batteries
- Exhausted batteries should be immediately removed from equipment and disposed of
- When discarding batteries with solder tags, insulate the tags by wrapping them with tape, foil, etc.

### Storage:

- Store unused batteries in their original packaging and keep them away from metal objects which may short-circuit them. Storing unpackaged cells together could result in cell shorting and heat build-up
- Store and display batteries in their original packaging in well ventilated, dry and cool conditions



# Jauch Battery Solutions

- Reliable energy for your application
- Standard cells and customized packs
- ESD protection
- Battery Certification Experts



RoHS compliant



Pb free



REACH compliant



Conflict Mineral free

- Avoid storing or display batteries in direct sun or in places where they get exposed to rain
- Do not stack battery cartons on top of each other exceeding a specified height. The height is clearly dependent on the strength of the packaging. As for general rule this height should not exceed 1.5 m for cardboard packages or 3 m for wooden cases. The above recommendations are equally valid for storage conditions during prolonged transit. Thus, batteries should be stored away from ship engines and not left for long periods in unventilated metal box cars (containers) during summer

## Section VIII – Exposure Controls / Personal Protection

Respiratory protection (specify type):	Not necessary under conditions of normal use (see section VI)
Ventilation:	Not necessary under conditions of normal use (see section VI)
Protective gloves:	Not necessary under conditions of normal use (see section VI)
Eye protection:	Not necessary under conditions of normal use (see section VI)
Other protective clothing or equipment:	Not necessary under conditions of normal use

In the event, however, electrolyte should be released by mechanical or electrical abuse, use:

<b>Respiratory protection</b>	Mask (with a filter preferably)
<b>Hand protection</b>	Synthetic rubber gloves
<b>Eye protection</b>	Goggles or glasses (see section VI)

## Section IX – Physical and Chemical Properties

The chemicals mentioned in Section II are contained in a sealed can. Under conditions of normal use, the chemicals will not be released.

Appearance:	Solid single cell
Nominal voltage:	Single cell: 3.6 volts

## Section X – Stability and Reactivity

Since batteries utilize a chemical reaction, they are actually considered a chemical product. As such, battery performance will deteriorate over time even if stored for a long period of time without being used.

However, lithium batteries are contained in a stable steel container and are sealed to avoid any chemical release under normal conditions of use.



# Jauch Battery Solutions

- Reliable energy for your application
- Standard cells and customized packs
- ESD protection
- Battery Certification Experts



RoHS compliant



Pb free



REACH  
compliant



Conflict  
Mineral free

Conditions to avoid: See Sections VII

---

## Section XI – Toxicological Information

---

The chemicals mentioned in Section 3 are contained in a sealed can.

Risk of exposure occurs only if the battery is mechanically or electrically abused or if it is ingested.

Inhalation, skin contact and eye contact are only possible, if the cell is opened. Exposure to corrosive fumes are irritating to skin, eyes and mucous membranes.

---

## Section XII – Ecological Information

---

The chemicals mentioned in Section III are contained in a sealed can. Under conditions of normal use, the chemicals will not be released.

It does not pose a physical or health risk to users, see section XIII for disposal.

---

## Section XIII – Disposal Considerations

---

Waste disposal method:

a) Be sure to comply with your federal, state and local regulation disposal of used batteries. Dispose in accordance with appropriate national and international regulations, below some references.

European Community: according to Directive 2002/96/EC on Waste Electrical and Electronic Equipment (WEEE), Annex II, batteries have to be removed from any separately collected WEEE. The removed batteries have to be treated according to the Battery directive 2006/66/EC.

US: Lithium batteries are neither specifically listed nor exempted from the Federal Environmental Protection Agency (US EPA) hazardous waste regulations. The only material of possible concern due to its reactivity is lithium metal.

Use a professional disposal firm for disposal of mass quantities of undischarged lithium batteries.

b) Open cells should be treated as hazardous waste

DO NOT INCINERATE or subject battery cells to temperatures in excess of 212°F (100°C). Such treatment can cause cell rupture.



# Jauch Battery Solutions

- Reliable energy for your application
- Standard cells and customized packs
- ESD protection
- Battery Certification Experts



RoHS compliant



Pb free



REACH compliant



Conflict Mineral free

## Section XIV – Transportation Information

Dangerous Goods Classification    Class 9 lithium batteries  
 UN-No.    UN 3090, UN3091  
 Proper Shipping Name:    Lithium Metal Batteries

Lithium-Metal cells and batteries are subject to the following transport rules:

Method	Technical Guidelines
Air	ICATO/IATA 62 <sup>nd</sup> Ed. 2021
Road and Rail Europe	ADR / RID 2021
Sea	IMDG Code 2021 (Amdmt.40-20)
USA	DOT 49 CFR

Please use the transportation information for reference. Exact packaging, shipping documentation and labelling requirements vary depending on energy content of cell/battery, quantity, method of shipping, airline or forwarder. Make sure to confirm concrete actions in advance with your shipping company.

All cells and batteries of Jauch Quartz GmbH mentioned under Section I and Annex fulfil the conditions pursuant to the requirements for partly regulated transportation. UN Manual of Tests and Criteria Part III Subsection 38.3 (DGR 3.9.2.6).

Lithium-Metal cells and batteries are forbidden for transportation aboard passenger aircrafts.

Battery cartons should be handled with care. Rough handling may result in batteries being shorted or damaged. This may cause leakage, explosion or fire.

## Section XV – Regulatory Information

- UN (United Nations): Recommendations on the Transportation of Dangerous Goods Model Regulations, Seventh revised edition, New York and Geneva 2019
- ICAO (International Civil Aviation Organization): Technical Instructions for the safety transport of dangerous goods by air 2020-2021
- IATA (International Air Transport Organization): Dangerous Goods Regulations 61<sup>st</sup> Edition; Effective January 1<sup>st</sup>, 2021
- ADR / RID 2021
- IMO (International Maritime Organization): International Maritime Dangerous Goods (IMDG) Code 2021 Edition (Amendment 40-20)
- EU Battery Directive 2006/66/EC and Amendments



# Jauch Battery Solutions

- Reliable energy for your application
- Standard cells and customized packs
- ESD protection
- Battery Certification Experts



RoHS compliant



Pb free



REACH  
compliant



Conflict  
Mineral free

---

## Section XVI – Other Information

---

Jauch lithium cells are registered under Underwriters Laboratories Inc. under UL file number MH62838.

This information has been compiled accurately to the best of our knowledge and belief. However, Jauch Quartz GmbH excludes any warranty for the accuracy, reliability or completeness of the information contained herein. It is the user's responsibility to satisfy himself as to the suitability and completeness of this information for his particular use.

Edition date: 15.02.2021





# Jauch Battery Solutions

- Reliable energy for your application
- Standard cells and customized packs
- ESD protection
- Battery Certification Experts



RoHS compliant



Pb free



REACH compliant



Conflict Mineral free

## Annex – list of Lithium-Thionyl-Chloride cells and content of lithium

Type	Class 9 (UN)	Lithium (gr.)
ER2450T		0.13
ER32L65J (1/10D)		0.25
ER32L100J (1/6D)		0.44
ER14250J-S		0.31
ER14335J-S		0.43
ER14505J-S		0.67
ER17505J-S		0.93
ER18505J-S		0.98
ER26500J-S	Class 9	2.20
ER34615J-S	Class 9	4.92