Temperature Accessories

Non-Contact Probes

80T-IR & 80PK-IR Infrared Temperature Probes

- Ideal for applications where object being measured cannot be touched
- Provides instant and highly repeatable readings
- 80T-IR (for DMMs) and 80PK-IR (for digital thermometers) have automatic shut-off after 10 minutes
- Senses infrared energy emitted by an object
- Measurement range: -18 to 260°C





Other Temperature Accessories


80CK-M & 80CJ-M type K & J Male Mini-Connectors

- Isothermal screw terminal for K or J wire
- Suitable for up to 20 guage thermocouple wire
- Color coded to industry standards (K-yellow, J-black)
- Two per package



Thermocouple Plug Kits 700TC1

A kit of 10 mini-plug connectors
Type J (black), one
Type K (yellow), one
Type T (blue), one
Type E (purple), one
Type R/S (green), one
Type B or CU (white), one
Type L (J-DIN) (blue), one
Type U (T-DIN) (brown), one
Type C (red), one



80AK

- Adapts Type-K thermocouple mini-connector to dual banana plug inputs
- Measurement range and accuracy: probe dependent
- Suitable for low voltage applications (below 30V AC, 60V DC)

80PK-EXT, 80PJ-EXT and 80PT-EXT Extension Wire Kits

- Extending and repairing J, K ot T-type thermocouple wires
- Kit includes 3 meters of thermocouple wire and 1 pair of male/female mini-connectors
- Maximum continuous exposure temperature : 260°C
- 80PK-EXT is compatible with K-type thermometers, 80PJ-EXT is designed for Jtype thermometers and PT-EXT for T-type thermometers



700TC2

A kit of 7 mini-plug connectors Type J (black), two Type K (yellow), two Type T (blue), one Type R/S (green), one



Temperature Probe Compatibility Chart																					ķ								ļS				
	300 / 7-600	10 / 11 / 12 / 12B		70 Series III	Series	21/75 Series III	77 Series	sries	8060A / 8062A	Series	85 Senes III	Corio	167 Series 189 Series	867B	39 / 41B	123	190 Series	43	45 508/50D	51/52/53/54 series II	33 / 3		712	713	714	617	717	718	724	725	741B	743B	744
Contact Probes	7	2 2	27	7	73	2	2	2	Φ C	8	85 2	-	= ==	8	ω	7	~	4	1			7	7			1 "	7 [7	7	7			1.
80PK-1 through 80PK-9		2	1	1	1	1	1	l	1	1	1 1	2				1	1	1	1	•					•				•	•	•	•	1
80T-150U			•	•	•	•	•	•	•	• •	• •		•	•		•	•	•											•	•	•	•	•
80PJ-1, 80PJ-9						ГП		. Τ.											•	•					•				•	•	•	•	•
8OPT-5A																									•		\perp		•	•	•	•	•
80BK		Ü		Т	T							1	•				. [1	L .									1_	
Non-Contact Probes																												Т	T				
8OT-IR				•	•	•	•	•	• (• (•		T -	•	•	•				•					T			•			• •
80PK-IR		2							\neg			2	2 2				\neg		•	•					•				•	•	•	•	• •
Miscellaneous	T		1	1	1					\neg									1								T						
80AK	T		1	1-	†				-+	_		1) •	1				十	\top							\neg							\neg
80TK		9 0			•	•	•	•	• •	•						•	•	•			1	•				•	\top		•	•	•	•	• •
80CK-M			Ť	+-	Ť	1	-		_			1	+-	1-							1-				•		\top	\top			•	•	•
80CJ-M			_	+	+	\Box	\neg		\dashv	\neg	+	+	+	1	-	† – †	_	_							ě	\top	\top	+	Ť		•	•	•
80PK-EXT, 80PJ-EXT			+-	+	+	+	-+			_	-+-	+	+	+	+-	\Box		_							ě	_	+	+-	1		•	•	•
80PT-EXT	tt-	_	1	+			\dashv	-+	$^{+}$	+	\top	Ť		+-	\vdash					•			\vdash	\Box	•	\top	\top	+	•	•	•	•	•

^{1:} Requires 80TK

^{2:} Requires 80AK