

TE Internal #: 2825210-1

Power Contacts, Contact, 600 VAC, Tin, 22 – 18 AWG Wire Size, .33

– .82 mm² Wire Size, Wire & Cable, Crimp, Power, Pin, -40 – 105 °C

[-40 – 221 °F]

View on TE.com >



Connectors > Power Connectors > Power Contacts











Power Contact Type: Contact
Operating Voltage: 600 VAC

Contact Mating Area Plating Material: Tin

Wire Size: .33 – .82 mm²

Features

Product Type Features

Connector & Contact Terminates To Electrical Characteristics Operating Voltage 600 VAC Contact Features Contact Mating Area Plating Material Tin Contact Current Rating (Max) 11 A Contact Type Pin	Power Contact Type	Contact
Operating Voltage 600 VAC Contact Features Contact Mating Area Plating Material Tin Contact Current Rating (Max) 11 A	Connector & Contact Terminates To	Wire & Cable
Contact Features Contact Mating Area Plating Material Contact Current Rating (Max) 11 A	Electrical Characteristics	
Contact Mating Area Plating Material Contact Current Rating (Max) Tin 11 A	Operating Voltage	600 VAC
Contact Current Rating (Max) 11 A	Contact Features	
	Contact Mating Area Plating Material	Tin
Contact Type Pin	Contact Current Rating (Max)	11 A
	Contact Type	Pin
Contact Retention Within Housing With	Contact Retention Within Housing	With
Mating Square Post Dimension 1.14 mm[.045 in]	Mating Square Post Dimension	1.14 mm[.045 in]
Contact Base Material Copper Alloy	Contact Base Material	Copper Alloy
Contact Mating Area Plating Material Thickness 2.54 µm[100 µin]	Contact Mating Area Plating Material Thickness	2.54 μm[100 μin]
Wire Contact Termination Area Plating Thickness 2.54 μm[100 μin]	Wire Contact Termination Area Plating Thickness	2.54 μm[100 μin]
Wire Contact Termination Area Plating Material Pre-Tin	Wire Contact Termination Area Plating Material	Pre-Tin
Contact Orientation Straight	Contact Orientation	Straight



Contact Underplating Material	Nickel
Contact Underplating Material Thickness	.762 μm[30 μin]
Termination Features	
Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Wire Insulation Support	Without
Dimensions	
Wire Size	.33 – .82 mm²
Compatible Insulation Diameter Range	1.5 – 3.1 mm[.06 – .122 in]
Usage Conditions	
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Operation/Application	
Circuit Application	Power
Packaging Features	
Packaging Method	Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2023 (233) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products



will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 2825208-1 VAL-U-LOK PIN 16AWG HCS SN LP



TE Part # 2825209-1 VAL-U-LOK SKT 16AWG HCS SN LP



TE Part # 2825212-1 VAL-U-LOK PIN HCS TN 22-18 LP



TE Part # 2825213-1 VAL-U-LOK SKT HCS SN 22-18 LP



TE Part # 2151096-1
OCEAN-2.0-APPLICATOR-S-062F125F



TE Part # 2238020-1 VAL-U-LOK PIN BR TN 22-18 LP



TE Part # 2-2151096-1 OCEAN-2.0-APPLICATOR-S-062F125F



TE Part # 2151096-2 OCEAN-2.0-APPLICATOR-S-062F125FA



TE Part # 5-2151096-1 OCEAN-2.0-APPLICATOR-S-062F125F



TE Part # 5-2151096-2 OCEAN-2.0-APPLICATOR-S-062F125FA



TE Part # 7-2151096-1 OCEAN-2.0-APPLICATOR-S-062F125F



TE Part # 7-2151096-2 OCEAN-2.0-APPLICATOR-S-062F125FA



Customers Also Bought






TE Part #2-1563759-1 18POS,AMP MCP1.5K,REC HSG,ASSY



TE Part #1418994-1 AMP MCP 2.8 HSG.WITH SEC.10POS



TE Part #3-520117-2 ULTRAFAST 250 ASSY REC 16-14 TPBR LP





TE Part #160917-2 FF 250 REC 1-2.5MM2 TPBR



TE Part #160860-2 FF 250 REC 0.5-1.0MM2 TPBR



TE Part #2825213-1 VAL-U-LOK SKT HCS SN 22-18 LP





TE Part #1-1969612-0 10P FH PLUG VAL-U-LOK V0



Documents

Product Drawings

VAL-U-LOK PIN HCS SN 18-22AWG

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2825210-1_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2825210-1_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2825210-1_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Power Contacts, Contact, 600 VAC, Tin, 22 – 18 AWG Wire Size, .33 – .82 mm² Wire Size, Wire & Cable, Crimp, Power, Pin, -40 – 105 °C [-40 – 221 °F]



Application Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English