


har-flex Power F ang 6P THR PL1 400pcs



Part number	15 65 006 2701 000
Specification	har-flex Power F ang 6P THR PL1 400pcs
HARTING eCatalogue	https://b2b.harting.com/15650062701000

Image is for illustration purposes only. Please refer to product description.

Version

Termination method	Reflow soldering termination (THR)
Connection type	Motherboard to daughtercard Extender card
Number of contacts	6
Details	According to IEC 61984, it is an unencapsulated connector. Protection against electric shock must be ensured by the type of installation by the user.
Pack contents	400 pieces on reel

Technical characteristics

recnnical characteristics	
Contact spacing (termination side)	2.54 mm
Contact spacing (mating side)	2.54 mm
Rated current	22 A
Rated voltage	180 V
Rated voltage	acc. to IEC 60664-1
Rated impulse voltage	1.5 kV
Pollution degree	2
Clearance distance	≥0.94 mm
Creepage distance	≥0.94 mm PCB ≥1.89 mm Connector
Insulation resistance	>10 ¹⁰ Ω
Contact resistance	≤25 mΩ
Limiting temperature	-55 +125 °C
Performance level	1
Mating cycles	≥500



Technical characteristics

Test voltage U _{r.m.s.}	0.84 kV
Isolation group	IIIa (175 ≤ CTI < 400)
Moisture Sensitivity Level (MSL)	1 acc. to ECA/IPC/JEDEC J-STD-020D
Process Sensitivity Level (PSL)	R0 acc. to ECA/IPC/JEDEC J-STD-020D
Coplanarity of contacts	0.1 mm

Material properties

Material (insert) Colour (insert) Black Material (contacts) Copper alloy Surface (contacts) Noble metal over Ni Mating side Sn over Ni Termination side Material flammability class acc. to UL 94 V-0 RoHS compliant ELV status compliant China RoHS e REACH Annex XVII substances Not contained REACH SVHC substances Not contained California Proposition 65 substances Not contained		
Material (contacts) Surface (contacts) Noble metal over Ni Mating side Sn over Ni Termination side Material flammability class acc. to UL 94 V-0 RoHS compliant ELV status China RoHS e REACH Annex XVII substances Not contained REACH SVHC substances Not contained REACH SVHC substances Not contained	Material (insert)	Liquid crystal polymer (LCP)
Surface (contacts) Noble metal over Ni Mating side Sn over Ni Termination side Material flammability class acc. to UL 94 V-0 RoHS compliant ELV status China RoHS e REACH Annex XVII substances Not contained REACH SVHC substances Not contained REACH SVHC substances Not contained	Colour (insert)	Black
Surface (contacts) Sn over Ni Termination side Material flammability class acc. to UL 94 RoHS compliant ELV status China RoHS e REACH Annex XVII substances Not contained REACH ANNEX XIV substances Not contained REACH SVHC substances Not contained	Material (contacts)	Copper alloy
RoHS compliant ELV status compliant China RoHS e REACH Annex XVII substances Not contained REACH ANNEX XIV substances Not contained REACH SVHC substances Not contained	Surface (contacts)	
ELV status compliant China RoHS e REACH Annex XVII substances Not contained REACH ANNEX XIV substances Not contained REACH SVHC substances Not contained	Material flammability class acc. to UL 94	V-0
China RoHS e REACH Annex XVII substances Not contained REACH ANNEX XIV substances Not contained REACH SVHC substances Not contained	RoHS	compliant
REACH Annex XVII substances Not contained REACH ANNEX XIV substances Not contained REACH SVHC substances Not contained	ELV status	compliant
REACH ANNEX XIV substances Not contained REACH SVHC substances Not contained	China RoHS	е
REACH SVHC substances Not contained	REACH Annex XVII substances	Not contained
	REACH ANNEX XIV substances	Not contained
California Proposition 65 substances Not contained	REACH SVHC substances	Not contained
	California Proposition 65 substances	Not contained

Commercial data

Packaging size	1
Country of origin	China
European customs tariff number	85366990
GTIN	5713140204744
eCl@ss	27460201 PCB connector (board connector)