

PRODUCT-DETAILS

F202 A S-63/0.5

F202 A S-63/0.5 Residual Current Circuit Breaker 2P A type 500 mA



General Information

| | |
|-----------------------|--|
| Extended Product Type | F202 A S-63/0.5 |
| Product ID | 2CSF202201R4630 |
| EAN | 8012542784609 |
| Catalog Description | F202 A S-63/0.5 Residual Current Circuit Breaker 2P A type 500 mA |
| Long Description | The RCCBs F200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications. |

Circular Value

| | |
|--|---|
| Circular Design Principles Recyclability Rate | Design for Closing Resource Loops - Standard EN45555 - 52,5 % |
| Sustainable Material Content | 0 % |
| End of Life Instructions | 9AKK108468A4361 |

Eco Transparency

| | |
|--|-----------------|
| Environmental Product Declaration - EPD | 9AKK108467A3700 |
|--|-----------------|

Technical

| | |
|--|--|
| Standards | IEC/EN 61008 UL 1053 |
| Type of Residual Current | A type |
| Rated Voltage (U_r) | 230 V |
| Rated Operational Voltage | 230 V |
| Rated Insulation Voltage (U_i) | 500 V |
| Rated Impulse Withstand Voltage (U_{imp}) | 4 kV |
| Input Voltage Type | AC |
| Rated Current (I_n) | 63 A |
| Rated Residual Current | 500 mA |
| Rated Conditional Short-Circuit Current (I_{nc}) | 10 kA |
| Rated Service Short-Circuit Breaking Capacity (I_{cs}) | 1 kA |
| Maximum Surge Current | 5 kA |
| Leakage Current Type | A |
| Rated Frequency (f) | 50 ... 60 Hz |
| Power Loss | at Rated Operating Conditions per Pole 3.2 W |
| Power Supply Connection | Arbitrary |
| Electrical Endurance | 10000 cycle |
| Number of Poles | 2 |
| Operating Characteristic | Selective |
| Mounting Type | DIN-Rail |
| Options Provided | None |
| Accessories Available | Yes |
| Connecting Capacity | Busbar 10 mm ² Rigid 25 ... 25 mm ² Flexible 25 ... 25 mm ² |
| Rated Cross-Section | 4 - Multi-Wired 0...25 mm ² 1 - Solid-Core 25...25 mm ² |

Environmental

| | |
|--|--|
| Ambient Temperature | -25...55 °C |
| Ambient Air Temperature | Operation -25...55 °C |
| Degree of Protection | IP2X |
| Pollution Degree | 2 |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 0.1 mm or 1 g - 20 cycles at 5...150...5 Hz |
| Resistance to Shock acc. to IEC 60068-2-27 | 25g 2 shocks 13 ms |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| RoHS Information | 9AKK106713A5602 |
| REACH Declaration | 9AKK108467A9482 |
| Environmental Information | Refer to RoHS |
| SCIP | 18f132b0-8f03-4611-9c59-dba03cc369bf Italy (IT) |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

Technical UL/CSA

| | |
|-------------------------------------|----------|
| Maximum Operating Voltage UL/CSA | 277 V AC |
| Short-Circuit Current Rating (SCCR) | 500 mA |

Dimensions

| | |
|-------------------------------------|----------|
| Width in Number of Modular Spacings | 2 |
| Product Net Width | 0.035 m |
| Product Net Height | 0.085 m |
| Product Net Depth / Length | 0.069 m |
| Product Net Weight | 0.200 kg |
| Built-In Depth (t ₂) | 69 mm |

Ordering

| | |
|------------------------------|-------------|
| Minimum Order Quantity | 1 piece |
| Package Level 1 Units | box 1 piece |
| Package Level 1 Gross Weight | 0.235 kg |
| Customs Tariff Number | 85363030 |
| Country of Origin | Italy (IT) |

Certificates and Declarations

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 9AKK106713A5602 |
|--------------------------------|-----------------|

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 9AKK107991A8329 |
| Instructions and Manuals | 9AKK107991A6127 |

Classifications

| | |
|------------------------------------|--|
| ETIM 8 | EC000003 - Residual current circuit breaker (RCCB) |
| ETIM 9 | EC000003 - Residual current circuit breaker (RCCB) |
| EPLAN Catalog Tree | Electrical engineering / Protection devices / Ground fault current circuit breaker |
| EPLAN Function Definition | Ground fault current circuit-breaker / Ground fault current circuit breakers, 4 connection points / Ground fault current circuit breaker, two-pole 1/2 2/1 3/4 4/3 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |
| CN8 | 85363030 |
| UNSPSC | 39121601 |
| eClass | V11.0 : 27142201 |
| IDEA Granular Category Code (IGCC) | 4875 >> Residual current circuit breaker (RCCB) |
| Object Classification Code | F |

Accessories

| Identifier | Description | Type | Quantity | Unit Of Measure |
|-----------------|--------------------------------------|---------------|----------|-----------------|
| 2CDS200912R0001 | S2C-H6R Auxiliary Contact | S2C-H6R | 2 | piece |
| 2CDS200922R0001 | S2C-S/H6R Signal / Auxiliary Contact | S2C-S/H6R | 2 | piece |
| 2CDS200946R0001 | S2C-H6-11R Auxiliary Contact | S2C-H6-11R | 1 | piece |
| 2CDS200946R0003 | S2C-H6-02R Auxiliary Contact | S2C-H6-02R | 1 | piece |
| 2CDS200946R0002 | S2C-H6-20R Auxiliary Contact | S2C-H6-20R | 1 | piece |
| 2CSS200933R0011 | F2C-A1 Shunt trip | F2C-A1 | 1 | piece |
| 2CSS200933R0012 | F2C-A2 Shunt trip | F2C-A2 | 1 | piece |
| 2CSS200911R0005 | S2C-UA 230 AC Undervoltage release | S2C-UA 230 AC | 1 | piece |
| 2CSS200911R0007 | S2C-UA 24 DC Undervoltage release | S2C-UA 24 DC | 1 | piece |
| 2CSS200911R0002 | S2C-UA 24 AC Undervoltage release | S2C-UA 24 AC | 1 | piece |
| 2CSS200911R0008 | S2C-UA 48 DC Undervoltage release | S2C-UA 48 DC | 1 | piece |
| 2CSS200911R0004 | S2C-UA 110 AC Undervoltage release | S2C-UA 110 AC | 1 | piece |
| 2CSS200911R0006 | S2C-UA 400 AC Undervoltage release | S2C-UA 400 AC | 1 | piece |
| 2CSS200911R0001 | S2C-UA 12 DC Undervoltage release | S2C-UA 12 DC | 1 | piece |
| 2CSS200911R0010 | S2C-UA 230 DC Undervoltage release | S2C-UA 230 DC | 1 | piece |
| 2CSS200911R0009 | S2C-UA 110 DC Undervoltage release | S2C-UA 110 DC | 1 | piece |
| 2CSS200911R0003 | S2C-UA 48 AC Undervoltage release | S2C-UA 48 AC | 1 | piece |
| 2CSS200910R0005 | S2C-OVP1 Overvoltage release | S2C-OVP1 | 1 | piece |
| 2CSS200993R0005 | S2C-OVP2 Overvoltage release | S2C-OVP2 | 1 | piece |
| 2CSF200997R0013 | F2C-CM Motor operating device | F2C-CM | 1 | piece |
| 2CSF200996R0013 | F2C-ARI Auto-reclosing unit | F2C-ARI | 1 | piece |

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Devices RCDs

