



Polymer Processing

PUR 300

MOULD RELEASE AGENT FOR RIGID INSULATION & SEMI-RIGID POLYURETHANES

PUR 300 is a highly effective, non-silicone mould release agent, based on a blend of waxes and hydrocarbon solvents. It has been specifically formulated to facilitate release of high density rigid polyurethanes and refrigeration/insulation foams.

PRODUCT CODES / FILL SIZES



31749 / 25Ltr



31750 / 200Ltr

APPLICATIONS

The product ensures a quick & easy release of high density rigid polyurethane foams & refrigeration foams from aluminium, steel and silicone rubber moulds.

DIRECTIONS

- Shake well before use and ideally keep 200 litre drums stirred continuously during use.
- Apply an even coating to the mould using a spray or paintbrush.
- Apply two coats onto new or clean moulds before first moulding and then re-apply as necessary.
- Due to the specially selected blend of waxes build up on the mould surfaces is minimal, however, it is recommended that moulds are cleaned regularly for best results.
- Ambersil Mould Cleaner is the ideal product for fast, efficient removal of any wax deposits.

TECHNICAL DATA (WITHOUT PROPELLANT)

Appearance	Milky suspension
Odour	Hydrocarbon
Specific Gravity (@ 25°C)	0.72
Temperature range	Release film to 100°C
Solubility	Soluble in solvents, insoluble in water
Viscosity	Thinner than water
Compatibility	Safe on metals and most synthetic materials
Flammability	Highly Flammable
Flashpoint	-4°C
Auto-ignition temperature	> 200°C

MATERIALS COMPATIBILITY

OK	-
CAUTION	-
NOT OK	-

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 3 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via info.uk@crcind.com

MISREPRESENTATION ACT 1967

TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 41
Created: July 2019
Updated: August 2021

CRC Industries UK Ltd.
Wylds Road, Bridgwater
Somerset, TA6 4DD
United Kingdom

t +44 (0)1278 727200
f +44 (0)1278 425644
e sales.uk@crcind.com
w www.crcurope.com

Company Registered No. 04910479

VAT No. GB 821 5195 42

