

Part Number : <u>1053251008</u> Product Description : Nano-Fit Terminal Position Assurance (TPA) Retainer, 2.50mm Pitch, 8 Circuits, Black Series Number : 105325 Status : Active Product Category : Connector Accessories



#### Drawings

Drawing 1053251008\_sd.pdf Packaging Design Drawing PK-105325-100-000.pdf

**3D Models and Design Files** 3D Model 1053251008\_stp.zip

#### Specifications

Application Specification AS-105300-100-001.pdf Product Specification PS-105300-100-001.pdf Test Summary 1053000000-TS-000.pdf

## **Product Environment Compliance**

#### Compliance

| GADSL/IMDS         | Not Relevant                                      |
|--------------------|---|
| China RoHS         | ©   |
| EU ELV             | Not Relevant                                      |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21                    |
| REACH SVHC         | Not Contained per D(2023)3788-DC<br>(14 Jun 2023) |
| EU RoHS            | Compliant per EU 2015/863                         |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C



- IPC 1752A Class D

- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

## **Part Details**

### General

| Status         | Active   |
|----------------|--|
| Category       | Connector Accessories  |
| Series         | 105325   |
| Description    | Nano-Fit Terminal Position<br>Assurance (TPA) Retainer, 2.50mm<br>Pitch, 8 Circuits, Black |
| Comments       | Operating temperature is -40° to<br>+105° for tin and -40° to +115° for<br>gold            |
| Component Type | Terminal Position Assurance  |
| Product Family | Nano-Fit Power Connectors  |
| Product Name   | Nano-Fit   |
| UPC            | 889056028615   |

# Physical

| Circuits (Loaded)             | 8                              |
|-------------------------------|--------------------------------|
| Circuits (maximum)            | 8                              |
| Color - Resin                 | Black                          |
| Lock to Mating Part           | Yes                            |
| Material - Resin              | Nylon                          |
| Net Weight                    | 0.200/g                        |
| Number of Rows                | 1                              |
| Packaging Type                | Bag                            |
| Temperature Range - Operating | -40° to +105°C, -40° to +115°C |

Use with Part(s)

| Description | Part Number |
|-------------|-------------|
|-------------|-------------|

| Nano-Fit TPA Capable Single Row<br>Receptacle Housings | 105307        |
|--|---------------|
| Nano-Fit TPA Capable Dual Row<br>Receptacle Housings   | <u>105308</u> |
| Nano-Fit TPA Capable Single Row<br>Plug Housings       | 200277        |
| Nano-Fit Dual Row TPA Capable<br>Plug Housings         | 201444        |

This document was generated on Nov 06, 2023