

Part Number: 349671001

Product Description: Mini50 Sealed

Receptacle, Single Row, with CPA, 10 Circuits, Polarization Option A, Black

Series Number: 34967

Status: Active

Product Category: Connector Housings



Documents & Resources

Drawings

Drawing 349671001_sd.pdf

3D Models and Design Files

3D Model 349671001_stp.zip

Specifications

Application Specification 348940001-AS-CH-000.pdf Application Specification AS-34894-0001-001.pdf Product Specification 349670001-000.pdf Test Summary 349670001-TS-000.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Duty-To-Declare |
|--------------------|--|
| China RoHS | • |
| EU ELV | Compliant per 2000/53/EC |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2023)3788-DC (14 Jun 2023) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------|---|
| Category | Connector Housings |
| Series | 34967 |
| Description | Mini50 Sealed Receptacle, Single Row, with CPA, 10 Circuits, Polarization Option A, Black |
| Application | Automotive, Power, Sealed, Wire- to-Board |
| Comments | -40°C to +105°C operating temperature for tin terminals; - 40°C to +125°C operating temperature for silver terminals |
| Product Family | Mini50 Connection Systems |
| Product Name | Mini50 Sealed |
| UPC | 889056793360 |

Physical

| Circuits (maximum) | 10 |
|--------------------------|------------|
| Color - Resin | Black |
| Gender | Receptacle |
| Glow-Wire Capable | No |
| Keying to Mating Part | Yes |
| Lock to Mating Part | Yes |
| Material - Resin | SPS/Nylon |
| Net Weight | 5.136/g |
| Number of Rows | 1 |
| Packaging Type | Bag |
| Panel Mount | No |
| Pitch - Mating Interface | 1.80mm |

| Pitch - Termination Interface | 1.80mm |
|-------------------------------|--------------------------------|
| Polarization | А |
| Polarized to Mating Part | Yes |
| Stackable | No |
| Temperature Range - Operating | -40° to +105°C, -40° to +125°C |

Mates With / Use With

Mates with Part(s)

| Description | Part Number |
|-------------|--|
| Mates With | Molex does not manufacture the mating header interface. To provide you with maximum design flexibility, we include the interface specification drawing with the part drawing, and a 3D model is available at the following URL so that you may design the interface into your device as you require: COMING SOON |

Use with Part(s)

| Description | Part Number |
|-----------------------------------|--------------|
| CTX50 Sealed Receptacle Terminals | <u>34905</u> |

This document was generated on Nov 06, 2023