ROLINE EV Charging Cable Assembly Type2, 3-Phase, 480VAC (3P+N+E), 32 A, 22 kW, 7.5 m

Product No. Manufacturer Manufacturer No. EAN (single piece) 19.08.0027 ROLINE 19.08.0027 7630049628144





Type2 charging cable for electric and hybrid cars with 22 kW, 3-phase, 480 V AC

- Enables easy / fast charging at public charging stations and private wall boxes (wallbox)
- Suitable for charging electric and hybrid vehicles
- Mode 3 / Type 2 car charging cable
- Connections: Type 2 on both sides
- For all electric cars with type 2 connection
- Ergonomically shaped plug and coupler
- Moisture protection (IP65 connected state, IP54 unconnected cable with protective caps attached)
- 32 A / 3- phase (480 VAC)
- Max. Charging power: 22 kW

| Technical specifications | | |
|--------------------------|------------------------------------|--|
| Manufacturer | ROLINE | |
| Product group | Power Cables | |
| Product type | Electric car charging cable | |
| Colour | black | |
| Length | 7.5 m | |
| Scope of delivery | E-car charging cable, carrying bag | |
| Charging power | 22 kW | |

| Current | 32 A |
|---------------------------------------|--|
| Number of phases | 3-phase |
| Supported charging technology | Mode-3 |
| Side 1 Connector Type | IEC 62196-2 Type 2 (VDE-AR-E 2623-2-2) |
| Side 1 Connector Gender | Male |
| Side 2 Connector Type | IEC 62196-2 Type 2 (VDE-AR-E 2623-2-2) |
| Side 2 Connector Gender | Female |
| Cable LSOH | flame retardant |
| Protection class (IP Code) | IP65 IP54 |
| Mains connection | IEC 62196-2 Type 2 plug, 3Ph. |
| Operating temperature min. | -30 °C |
| Operating temperature max. | 50 °C |
| Height | 40 mm |
| Width | 390 mm |
| Depth | 390 mm |
| Weight | 2.6 kg |
| Height of packaging (single piece) | 100 mm |
| Width of packaging (single piece) | 370 mm |
| Depth of packaging (single piece) | 370 mm |
| Package weight (single piece) | 5 kg |