

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of GRM32EC80G227ME05# from the official website of Murata Manufacturing Co., Ltd.

"#" indicates a package specification code.

http://www.murata.com/en-gb/products/productdetail?partno=GRM32EC80G227ME05%23

GRM32EC80G227ME05K

In Production RoHS REACH 105

< List of part numbers with package codes > GRM32EC80G227ME05L
GRM32EC80G227ME05K

Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
Specific Applications	Consumer equipment,Industrial Equipment,Mobile Electronics,Medical equipment [GHTF A/B/C] except for implant equipment,Automotive infotainment/comfort equipment Please refer to Our Website and specifications, etc. for information about the performance, functions, quality, management, and safety required for the above applications, and use Products after confirming the performance and reliability of the actual Product.


References

		Standard
Packaging	Specifications	Packing
		Quantity
L	180Embossed Tape	1000
К	330Embossed Tape	4000

ass (typ.)	
1 piece	110.0mg

Appearance & Shape





1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





GRM32EC80G227ME05K

Note: This datasheet may be out of date. Please download the latest datasheet of GRM32EC80G227ME05# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=GRM32EC80G227ME05%23

"#" indicates a package specification code.



Specifications

Length	3.2±0.3mm
Width	2.5±0.3mm
Thickness	2.5±0.3mm
Capacitance	220µF ±20%
Distance between external terminals g	1.0mm min.
External terminal size e	0.3mm min.
Operating Temperature Range	-55℃ to 105℃
Rated Voltage	4Vdc
Size code in inch(mm)	1210 (3225M)
Capacitance change rate	±22.0%
Temperature characteristics (complied standard)	X6S(EIA)
Temperature range of temperature characteristics	-55℃ to 105℃

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

