

VATOR IN ELECTRONICS

GRJ31BR7LV153KW01K

Note: This datasheet may be out of date.

Please download the latest datasheet of GRJ31BR7LV153KW01# from the official website of Murata

http://www.murata.com/en-gb/products/productdetail?partno=GRJ31BR7LV153KW01%2

"#"at the end indicates the package specification code.

















< List of part numbers with package codes > GRJ31BR7LV153KW01L GRJ31BR7LV153KW01K



Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
Specific Applications	Consumer equipment,Industrial Equipment,Mobile Electronics,Medical equipment [GHTF A/B/C] except for implant equipment,Automotive infotainment/comfort equipment Please refer to Our Website and specifications, etc. for information about the performance, functions, quality, management, and safety required for the above applications, and use Products after confirming the performance and reliability of the actual Product.



Manufacturing Co., Ltd.

Notices

Derating6. Resin external electrode products



References


		Standard
Packaging	Specifications	Packing
		Quantity
L	180Embossed Tape	3000
К	330Embossed Tape	10000

Mass (typ.)	
1 piece	40.0mg



Appearance & Shape





1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





GRJ31BR7LV153KW01K

Note: This datasheet may be out of date.

Please download the latest datasheet of GRJ31BR7LV153KW01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=GRJ31BR7LV153KW01%23

"#"at the end indicates the package specification code.



Specifications

Length	3.2±0.2mm
Width	1.6±0.2mm
Thickness	1.25+0/-0.3mm
Capacitance	15000pF ±10%
Distance between external terminals g	1.2mm min.
External terminal size e	0.3mm min.
Operating Temperature Range	-55°C to 125°C
Rated Voltage	630Vdc
Size code in inch(mm)	1206 (3216M)
Capacitance change rate	±15.0%
Temperature characteristics (complied standard)	X7R(EIA)
Temperature range of temperature characteristics	-55°C to 125°C

2 of 2

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

