

# GRJ31CR72J223KWJ3K

Note: This datasheet may be out of date.

Please download the latest datasheet of GRJ31CR72J223KWJ3# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=GRJ31CR72J223KWJ3%23

"#"at the end indicates the package specification code.















< List of part numbers with package codes > GRJ31CR72J223KWJ3L GRJ31CR72J223KWJ3K




## **Applications**

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
Specific Applications	Consumer equipment, Industrial Equipment, Mobile Electronics, Medical equipment [GHTF A/B/C] except for implant equipment, Automotive infotainment/comfort equipment Please refer to Our Website and specifications, etc. for information about the performance, functions, quality, management, and safety required for the above applications, and use Products after confirming the performance and reliability of the actual Product.



## Appearance & Shape







### **Notices**

Resin external electrode products



### References

Packaging	Specifications	Standard Packing Quantity
L	180Embossed Tape	2000
К	330Embossed Tape	8000

Mass (typ.)	
1 piece	52.0mg

1 of 2

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





# GRJ31CR72J223KWJ3K

Note: This datasheet may be out of date.

Please download the latest datasheet of GRJ31CR72J223KWJ3# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-qb/products/productdetail?partno=GRJ31CR72J223KWJ3%2

"#"at the end indicates the package specification code.



# **Specifications**

Length	3.2±0.2mm
Width	1.6±0.2mm
Thickness	1.6±0.2mm
Capacitance	22000pF ±10%
Distance between external terminals g	1.2mm min.
External terminal size e	0.3mm min.
Operating Temperature Range	-55°C to 125°C
Rated Voltage	630Vdc
Size code in inch(mm)	1206 (3216M)
Capacitance change rate	±15.0%
Temperature characteristics (complied standard)	X7R(EIA)
Temperature range of temperature characteristics	-55°C to 125°C

2 of 2

### Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

