D-Sub ConnectorWith Backshell Kit, 15 Ways

multicomp PRO





Specification

Backshell Material

Backshell : Die Cast Zinc Alloy

Plating : Nickel

Jackscrews : Steel, Zinc Plated
M3 Hoodscrews : Steel, Zinc Plated
Compression Insert : ABS, UL Recognized
Compression Spring : Steel, Nickel Plated
Operating Temperature : -40°C to +120°C

Rated voltage : 250V Rates current : 5A

Contact resistance : 20MΩ max

Insulation resistance : $1000M\Omega$ min.at 500V DC

Withstand voltage : 500V Per mintute
Temperature range :-55°C to 105°C

Connector Material

Plastic : PBT+30% GF (UL94V-0), Black

Terminal : Brass, tin-gold plated

Backshell Kit Includes


Backshell Halves : 02 pcs 4-40 Thumbscrews : 02 pcs Housing Screws : 02 pcs Set Of Compression Inserts - Various Sizes : 01 pc


Diameters 4mm (0.157"), 5mm (0.167"),

7mm (0.276"), 9mm (0.354")


Compression Spring : 01 pc

Diagram









Dimensions							
Size	A ±0.5 (±0.02)	B ±0.5 (±0.02)	C ±0.5 (±0.02)	D ±0.25 (±0.01)			
15	39.5 (1.555)	41.5 (1.634)	15 (0.591)	33.32 (1.312)			


Dimensions: Millimetres (Inches)


Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro



D-Sub Connector With Backshell Kit, 15 Ways







Part Number	Α	В	С	D
MP013641	39.2	33.3	24.66	27.5

Part Number Table

Description	Part Number	
D-Sub Connector with Backshell Kit, 15 Ways, Receptacle	MP013641	

Dimensions: Millimetres (Inches)

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

