Sensor Cable Assembly multicomp

IP67 Immersed in 1M water for 30 Minutes






Specification

Waterproof Rate

Test Conditions

Current Rating Rated Constant Voltage Conduct Resistance **Hi-POT** Test Insulation Resistance Durability Mating And Unmating Force **Corrosion Resistance Rated Temperature** Rated Humidity Flame Rating

Diagram



: IP67

: 3A

: 60V DC

: 10mΩ max.

: 30 to 60N

: 500V AC, 0.5mA (1Sec)

: 20MΩ Min. By 500V DC : 200 Cycles Min.

: Salt Spray Test, 48H

: -25°C to +70°C

: 95% (40°C)

: UL94V-0

CONN.

CONN.

BROWNORANGE BLACK WHITE CRAN GREEN PURPLE YELLOW RED FINK BLUE

> Pin Assignments Front View

No.	Description	Qty.	Material	Plating & Color
А	Cable	1	FEP, PVC 11C × 0.2mm ² OD=6 ±0.1	Black
В	Molding		PVC	

Part Number Table

	Description	Part Number	
mensions : Millimetres	M11 Sensor Cable, 3A, 11 Pin, Male Connector	MP013720	

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

