

Product Search Data Shee

Note: This datasheet may be out of date.

Please download the latest datasheet of MPQ0125V3NBMC from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=MPQ0125V3NBMC

MPQ0125V3NBMC



Recommended

New





Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
	Consumer equipment,Industrial	
	Equipment	
	Please refer to Our Website and	
	specifications, etc. for information about	
Specific	the performance, functions, quality,	
Applications	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	
Recommended	Base Station	
Applications	Dase Station	



Features

12V, 257A, Single Output, Quarter -Brick, 18-75V Input Range, Negative Logic, Baseplate, PMBus, RoHS.



Appearance & Shape



1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

 $2. This \ data{sheet has only typical specifications because there is no \ space for \ detailed \ specifications.}$

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of MPQ0125V3NBMC from the official website of Murata $\,$ Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=MPQ0125V3NBMC

MPQ0125V3NBMC



Specifications

Output power (W)Max	300W
Vin(V)	18V to 75V
Vin(V)typ	48V
Vout(V)	9.6V to 13.2V
Vout(V)typ	12V
LineRegulation (%)	-0.02%
LoadRegulation (%)	-0.02%
Isolation Voltage (V)	2250V
Efficiency (%)	94%
Size(mm)W	36.8mm
Size(mm)L	58.4mm
Size(mm)T	14.4mm
Operatingtemperature(degC)	-40°C to 85°C
Outputs (#)	1
lout(A)Max	25A
Form	1/4tr Brick
Package	DIP
Productseries	MPQ300W
Product Series Features	MPQ300, 1/4tr Brick
Regulation	Regulated
Safety Approval	UL-62368-1
Brand	Murata Power Solutions

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

