

Johanson Product Information for VPEH501W474K1GV001E

Johanson Company: Johanson Dielectrics inc.	Product Release Date: 04 January, 2006
Deprecated P/N: 501S48W474KV4E	Web Page Link: https://www.johansondielectrics.com/high-voltage- mlc-capacitors
Datasheet Date: 04-15-2024	
Description: Capacitors HVS PME, 2225, X7R, 500V, 0.47µF±10%, Ni/Sn (RoHS), 7" Reel Embossed Tape	Size for Capacitors (EIA): 2225
	Thickness (Max): 0.160
Life Cycle Stage: Active - Production	End Band (Min):
Schedule B: 8532	End Band (Max):
ECCN: EAR99	Standard Item: 1
RoHS Compliance: Yes, RoHS 10/10	Lead Time Typical (Weeks)*: *This can vary significantly so it is important to obtain a quotation with lead time for production planning purposes. 10
REACH: 1	
Country of Origin: US	Length (Min): 0.215
Product Family: Capacitors	Length (Max): 0.235
Product Subfamily: Capacitors High Voltage PME SMD ? 500V	Width (Min): 0.240
Capacitance Value: 0.470	Width (Max): 0.270
Cap Unit of Meas: μF	Packaging: 7" Reel Embossed Tape
Tolerance: ±10%	Operating Temp Range: -55°C to +125°C
Voltage: 500.0	Storage Temp Range (Packaged): -65°C to +125°C
Dielectric Temp Coefficient: X7R	Storage Temp Range (Non Operating): +5°C to +40°C with RH 20% to 70%
Termination: 68	
Marking: No Mark	