

MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

# Mikromedia 5 for STM32F7 Resistive FPI with frame



PID: MIKROE-6159

### **Rich with peripherals**

Mikromedia 5 for STM32F7 Resistive FPI with frame is not limited to multimedia-based applications only. USB, WiFi and RF connectivity options, digital motion sensor, battery charging functionality, piezo-buzzer, SD card reader, RTC, and much more expands its use beyond the multimedia.

Mikromedia 5 for STM32F7 Resistive FPI with frame has three mikroBUS™ Shuttle connectors, a brand-new addition to the mikroBUS<sup>™</sup> standard in the form of a 2x8-pin IDC header with 1.27mm (50mil) pitch. mikroBUS<sup>™</sup> Shuttle extension board is an add-on board equipped with the conventional mikroBUS<sup>™</sup> socket, which ensures compatibility with 894 <u>Click boards<sup>™</sup></u>.

#### Awesome graphics on MCU driven TFT

Mikromedia 5 for STM32F7 Resistive FPI with frame is a compact development board designed as a complete solution for the rapid development of multimedia and GUI-centric applications. By featuring a 5" TFT display with resistive touch screen driven by the powerful graphics controller that can display the 24-bit color palette (16.7 million colors), along with a DSPpowered embedded sound CODEC IC, represents a perfect solution for any type of multimedia application.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.

ISO 27001: 2013 certification of informational security management system. ISO 14001: 2015 certification of environmental management system. OHSAS 18001: 2008 certification of occupational health and safety management system.

Mikroe produces entire development toolchains for all major microcontroller architectures.



ISO 9001: 2015 certification of quality management system (QMS).



Time-saving embedded tools

MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

#### Develop-on & build-in the same board

Mikromedia 5 for STM32F7 RESISTIVE FPI (FPI stands for Front Panel Integration) with frame is designed as the complete solution. It can be implemented directly into any project, with no additional hardware modifications. At its core, there is a powerful 32-bit <u>STM32F407ZGT6</u> microcontroller from <u>STMicroelectronics</u>, which provides sufficient processing power for the most demanding tasks. Board has a TFT display with a metal frame, and four mounting holes that enable simple installation in various kinds of industrial appliances. For most uses, a nice casing is all that is needed to turn this product into a high-performance, feature-rich device. This board requires the use of an external programmer and debugger, preferably <u>CODEGRIP</u> or mikroProg. The microcontroller can be programmed and debugged over the JTAG/SWD compatible 2x5 pin header, labeled as <u>PROG/DEBUG</u>.

Mikroe produces entire development toolchains for all major microcontroller architectures. Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system. ISO 14001: 2015 certification of environmental management system. OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).



MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

## Specifications

Туре	mikromedia
Architecture	ARM (32-bit)
Display size	5"
Resolution	800x480px
Graphic controller	SSD1963
Touch Screen	Resistive
Input Voltage	3.3V
Silicon Vendor	STM
mikroBUS No.	3
Frame Type	Metal Frame
Features	Batt. Chg. when OFF,WiFi,USB Type C,USB Host,SD Card,RF,ON/OFF switch,MP3,External DC source,Battery Powered
Display type	mikromedia

#### Downloads

Mikromedia 5 for STM32F7 Resistive FPI with frame manual

Mikromedia 5 for STM32F7 Resistive FPI with frame schematic

Mikromedia 5 for STM32F7 Resistive FPI with frame 2D and 3D files

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system. ISO 14001: 2015 certification of environmental management system. OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).