Miniature Toggle Switches multicomp PRO



Specifications

Dielectric Strength

Mechanical Life : 100,000 make-and-break cycles DC 10V & 0.1mA.

- Contact Resistance : 10mΩ max. Insulation Resistance
 - : 500V 500MΩ min.

: 1,000 Vrms min.@sea level.

Operating Temperature : -40°C to 85°C.

Materials

Case Actuator Bushing Housing


Terminal/Contact


: Brass, Chrome Plated

: Diallyl phthalate (DAP) (UL94V-0)

- : Brass, Nickel Plated
- : Stainless Steel : Brass

Diagram





SOLDER LUG

	Contact Plating	Terminal Plating	Ratings	
Q	Silver	Slver	6A @ 125V AC	
С	Gold over Silver	Gold over silver	3A @ 250V AC or 28V DC	
R	Gold	Gold	0.4 Volt-Amps (VA) max. @20V max. (AC or DC)	

RoHS

Compliant


Switch Function

	Pos.1	Pos.2	Pos.3
Model		-	4
MP1FS5T1B6M1QES-5	ON	OFF	(ON)
Term. Comm.	2-3		2-1
Schematic	1 2 Comm 3	OPEN	2 Comm. 0 3

Dimensions : Inches (Millimetres)

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro





Part Number Table

	Description	Part Number
Dimensions : Inches (Millimetres)	Toggle Switch, On-Off-(On), Solder Lug	MP1FS5T1B6M1QES-5

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility for such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

