## 1800-07G-K1L-B

( Home: Products: Sensors: Pressure Sensors - Board Mount: Low Pressure Sensors: 1800/1805)



1800/1805 Series, 0 psi to 30 psi pressure range, gage, 1.5 mA typ., 2 mA max. supply current, TO-8 can  $\,$ 

Actual product appearance may vary.

Measurement Type	Product Specifications  Gage
Pressure Range	0 psi to 30 psi
Supply Current	1.5 mA typ., 2.0 mA max.
Temperature Compensation	Yes
Top Side Overpressure	250 psi
Response Time	1 ms
Bottom Side Overpressure	50 psi
Package Type	TO-8 Can
Full Scale Span	40 mV to 120 mV
Insulation Resistance	100 mOhm at 50 Vdc
Repeatability	±0.0125 max. %FFS
Output Resistance	3.5 kOhm min., 6.0 kOhm max.
Common Mode Voltage	50% input
Shock	100 g for 11 ms
Vibration	10 g rms at 20 Hz to 200 Hz
Pressure Connection	3/16 in hole (top); 1/8 in tube (bottom)
Operating Temperature	-40 °C to 121 °C [-40 °F to 257 °F]
Compensated Temperature Range	-1 °C to 54 °C [34 °F to 129 °F]
Media Compatibility	Clean, dry gases only.
UNSPSC Code	41111927
UNSPSC Commodity	41111927 Pressure Sensors
Life	100 million cycles
Availability	Global
Series Name	1800/1805