## ALPHA WIRE COMPANY CUSTOMER PRODUCT SPECIFICATION

Part Number: 2400C Issue: 6

Page 1 of 1 Pages Issue Date: 11/3/2008 Effective Date: 11/10/2008

A. Construction <u>Diameters (In)</u>

) Component 1 2 X 1 COND a) Conductor 24 (7/32) AWG TC

b) Insulation 0.016" Wall, Nom. Polyethylene(PE) 0.056

(1) Color(s)

Cond	Color	Cond	Color	Cond	Color
1	BLACK	2	NATURAL		

2) Cable Assembly 2 Components Cabled a) Twists: 8.0 Twists/foot (min)

3) Shield: Alum/Mylar Tape, 25% Overlap, Min.

a) Foil Direction Foil Facing Out
b) Drain Wire 24 (7/32) AWG TC

4) Jacket 0.020" Wall, Nom., PVC 0.156 (0.166 Max.)

a) Color(s) SLATE

b) Print ALPHA WIRE-\* P/N 2400C 2C 24 AWG

SHIELDED 75C (UL) TYPE CMG OR AWM 2092 ----

C(UL) CMG FT4 ROHS

\* = Factory Code

**B.** Industry Approvals

1) UL AWM/STYLE 2092 60°C / 300 V<sub>RMS</sub>

VW-1

CMG 75°C

) CSA International FT4

C(UL) TYPE CMG 75°C

3) EU Directive 2002/95/EC(RoHS):

All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for compliance Date of Manufacture.

4) California Proposition 65:

The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65.

## C. Physical & Mechanical Properties

1) Temperature Range -20 to 75°C

2) Bend Radius3) Pull Tension10X Cable Diameter10.6 Lbs, Maximum

D. Electrical Properties (For Engineering purposes only)

1) Voltage Rating 300 V<sub>RMS</sub>

2) Capacitance 17.8 pf/ft @1 kHz, Nominal Conductor to Conductor

3) Ground Capacitance 32 pf/ft @1 kHz, Nominal

4) Characteristic Impedance 87 Ω

5) Inductance 0.22 µH/ft, Nominal

6) Conductor DCR
 7) OA Shield DCR
 25 Ω/1000ft @20°C, Nominal
 19.5 Ω/1000ft @20°C, Nominal

## E. Other

1) Packaging

- a) 1000 FT
- b) BOX 1000FT
- c) BOX 500FT
- d) 500 FT
- e) 100 FT

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

## ALPHA WIRE COMPANY CUSTOMER PRODUCT SPECIFICATION

Part Number: 2400C Issue: 6

Page 2 of 1 Pages Issue Date: 11/3/2008 Effective Date: 11/10/2008

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.